



# Technical Data

## **Cleaner Degreaser** Industrial Strength Cleaner



### **TYPICAL PROPERTIES**

COLORS: clear

COVERAGE: 100sq.ft./quart; 400sq.ft./gallon.

### **Application Information**

Proper surface preparation is essential to achieve a high quality finish. Wear proper protection, which may include gloves, eye protection, and/or other protective devices.

POR-15® Cleaner Degreaser represents a revolutionary breakthrough in metal cleaners. It is non-flammable, water-based, and has no noxious odors, chlorinated solvents, or petroleum products.

Cleans and degreases metal, plastic, wood, fiberglass, and painted surfaces including engines, fuel tanks and transformers. Also works well on closed systems including air conditioning, boiler tubes, compressor lines, heat exchangers and coils.

**IMPORTANT:** POR-15® Cleaner Degreaser is designed to be diluted. The substrate and the degree of degreasing necessary will dictate the level of dilution. 1:1 is best for engine cleaning, removing baked-on oil from cylinder heads, removing gum and varnish from fuel tanks. To clean exterior surfaces of cars or boats, use dilutions beginning at 1 part POR-15® Cleaner Degreaser to 5 parts water through to 10 parts water. Always remember to thoroughly rinse off POR-15® Cleaner Degreaser with water after completing your cleaning job.

### **Safety Information**

**CAUTION!** MAY BE HARMFUL IF SWALLOWED. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.

Harmful by inhalation, in contact with skin and if swallowed. Do not breathe vapor or mist. Do not ingest. Do not get in eyes or on skin or clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.

**FIRST AID:** If affected by inhalation of vapors or spray mist, remove to fresh air. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and call a physician; for skin, wash thoroughly with soap and water. In case of ingestion, DO NOT induce vomiting. Get medical help immediately.

**IN CASE OF SPILL** – Absorb with inert material and dispose of in accordance with applicable regulations.

**DISPOSAL:** The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.. Local requirements vary; contact your state-designated environmental agency for information concerning re-use, recycling, or disposal of solvent-borne paint.

Refer to Material Safety Data Sheet available from your dealer for further safety and handling information.



Absolute Coatings, Inc.  
38 Portman Rd, New Rochelle, NY 10801

**800-457-6715**  
**www.AbsoluteCoatings.com**