



Refinishing Course Primer



Product: Automotive Art 1K Primer - Aerosol, 15001

Features:	<ul style="list-style-type: none"> It is a 1K primer It is in aerosol form 	
Benefits:	<ul style="list-style-type: none"> Fast drying It can be applied to small and medium repair areas Does not require any preparation, again improving productivity 	
Recommended Use:	Automotive Art 1K Primer Aerosol can be used in small to medium repairs in the refinishing industry	
Materials and tools for the job:	<ul style="list-style-type: none"> Automotive Art 1K Primer Aerosol 	
Pretreatment:	Sand surface with P360 sand paper, then clean with Automotive Art Universal Cleaner	
Mixing ratio: Hardener	Ready to use	
Nozzle size:	N/A	
Spraying Pressure:	N/A	
Application:	Shake the aerosol before use for 2-3 minutes after hearing the sound of mixer inside of the can.	
Drying time: At 20° C At 60° C IR short wave	<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;">25 min</div> <div style="text-align: center;">15 min</div> </div>	
Sanding:	P 600-800 Wet by hand	P 400-500 Orbital sander
Pot life at 20° C:	N/A	
Warnings:	After use, clean the nozzle by turning the aerosol upside down and spray until only gas emerges.	