




Technical Data Sheet

Pre-Treatment

Product: Automotive Art Universal Cleaner, 20-95

Features:	This product is good for the removal of wax, silicone and grease to ensure that the surface is clean for the job.	
Benefits:	It promotes adhesion and eliminates the possibility of defects in paint finishes (fish eyes defect - craters). Easy to apply and very economical.	
Recommended Use:	This product is recommended to use in preparing surfaces for priming and painting.	
Materials for the job:	Clean white lint free cloth. Spray bottle.	
Physical Properties:	Specific gravity (kg/l):	0.79
	Flash point:	Closed cup: >124°C (>255°F)
	Vol.% solids:	0
	Coverage:	-
	Viscosity:	-
	Gloss:	-
	Color:	Clear
	V.O.C. (RTS):	790 g/l (6.6 lbs/gal)
Pretreatment:	Mechanically remove rust by dry sanding with P80 / 120 dry - use wire brush for difficult areas. Or by sand blasting.	
		
Cleaning the equipment:	Lacquer Thinner 60-4	
Shelf Life:	Under normal storage conditions minimum two years (unopened tins).	
Application:	Apply Automotive Art Universal Cleaner 20-95 on areas to be worked on using: <ul style="list-style-type: none"> ▪ One cloth and wipe off immediately with second clean cloth. ▪ Or spray bottle and wipe off immediately with a clean cloth. For surfaces with lots of grease and silicone, repeat the process as needed. <u>Work on small areas at a time.</u>	
Warnings:	Use extreme caution when applying product to NC lacquer and base coat metallic surfaces as these surfaces are sensitive to this product and may result in the damage or removal of such surfaces	

