

# SEALERS & FOAMS



## SEALERS AND FOAMS

The PLIOGRIP by Valvoline high-performance line of Sealers and Foams provides body shops with a complete package to finish the repair.

PLIOGRIP by Valvoline Sealers and Foams are easy to work with and yield fantastic results:

- 1K Seam Sealer – A permanently flexible, moisture-cured seam sealer for standing seams, floor pans, trunks, wheel wells and more, for an OEM-matching brushed, bead or sprayed texture
- 2K Seam Sealer – our new 2K epoxy seam sealers can be painted immediately
- Rigid and Flexible Foam – Rigid and flexible NVH foams with 5 seconds of work time or less, these foams match OEM materials without unwanted structural pressure

All PLIOGRIP by Valvoline Sealers and Foams offer excellent adhesion, no shrinkage and a lifetime warranty.

## THE SYSTEM

Our Sealers and Foams are part of a family of versatile, fast-acting, smooth-finishing PLIOGRIP by Valvoline products.

PLIOGRIP by Valvoline. Easier to use. Faster to cure. Proven to perform.

## SEALERS

- Easy to tool out
- Non-sag, no shrinkage
- Excellent adhesion to primed metal
- Lifetime warranty

## FOAMS

- 10x expansion
- Excellent adhesion to primed metal
- No shrinkage or unwanted structural pressure
- Lifetime warranty
- Non-flammable

Product	Application	Sizes	Stock No.	Work Time	Sand Time	Paint Time
<b>Non-Sag Seam Sealer 6</b>	Non-sag 2K seam sealer. Duplicates OEM tape and brushed seams.	220ml	8008	6 minutes	30 minutes	Immediately, scuff after 30 minutes.
<b>High-Body Seam Sealer 12</b>	Non-sag 2K seam sealer. Duplicates OEM tapes and brushed seams.	220ml	8009	12 minutes	30 minutes	Immediately, scuff after 30 minutes.
<b>Self-Leveling Seam Sealer 12</b>	Self-leveling sealer. Duplicates OEM puddle seams and roof ditches.	220ml	8010	12 minutes	30 minutes	Immediately, scuff after 30 minutes.
<b>Controlled-Flow Seam Sealer 6</b>	Higher body flowable sealer for tape seams with round edges often seen on imports.	220ml	8050	6 minutes	30 minutes	Immediately, scuff after 30 minutes.
<b>Flexible PUR Sealer</b>	White, flexible 1K non-sag seam sealer. Duplicates OEM taped and brushed seams	310ml tube	8011	20 minutes	N/A	Immediately – 6 hours.
<b>Sprayable MSP Sealer</b>	Black or White, sprayable 1K textured spray seam sealer. Duplicates OEM wheel wells, trunk, floor pan, and apron seams.	310ml tube (black) 310ml tube (white)	8012 8013	20 minutes	N/A	Immediately – 4 days.
<b>NVH Flexible Foam</b>	Black expandable foam for intrusion beams and rockers. Duplicates OEM applications.	220ml	8014	3-10 second Foam Time	N/A	N/A
<b>NVH Rigid Foam</b>	Cream color expandable foam for pillars. Matches OEM materials without unwanted structural pressure.	220ml	8015	10-15 second Foam Time.	N/A	N/A

All data taken at 23°C (74°F)

BODY REPAIR SYSTEM FROM ASHLAND

©Registered trademark, Ashland. ©Copyright 2007, Ashland. (R9/07) www.pliogripbyvalvoline.com