

## 2" AND 3" GRINDING DISCS



Durable backing and tough abrasives; great combination to tackle welds and rust removal

CARBO™  
**FIBRATEx**®



### Fibratex Flex-Loc TR Surface Blending Discs



Ideal for removing rust and oxides, blending out disc marks, and removing coatings and gasket residues from automotive surfaces. Thick, reinforced non-woven backing is impregnated with tough aluminum oxide abrasive. Advanced resin system will not smear.

		 2" TR	 3" TR
GRIT	COLOR	055395-	055395-
Very Fine – 320	Blue	12506	12509
Medium – 120	Maroon	12507	12510
Coarse – 80	Brown	12508	12512
<b>CASE</b>		<b>50</b>	<b>25</b>



### Carbo Fire Flex-Loc TR Surface Blend Discs




Ideal for removing surface rust, blending out grind marks, and removing coatings from automotive surfaces and will not smear. Carbo Fire Surface Blend can also be used to remove seam sealer and undercoating without loading. The discs are thin enough to get into tight spots but durable enough to last. Carbo Fire ceramic grain ensures a fast cut with long life. Surface Blend TR can be used on the face, side, and back.

	 2" TR	 3" TR
DESCRIPTION	055395-	055395-
Carbo Fire	53332	53333
<b>CASE</b>	<b>10</b>	<b>10</b>



### Flex-Loc TR Back-Up Pads



Flex-Loc TR are compatible with similar competitive attachment systems.

	 1" Back-up Pad	 2" Back-up Pad	 3" Back-up Pad
DESCRIPTION	088341-	662610-	662610-
Flex-Loc TR	64037	55103	55105
<b>CASE</b>	<b>1</b>	<b>10</b>	<b>10</b>



### Carbo-Cut Grinding Discs

Zirconia grain is resin bonded to a unique backing which resists cracking and breaking and can be cut down up to the 1" core. Use the cores to grind "pinch" welds and other hard to reach areas. The 1/4" quick change mandrel is for use on automotive drills.

	 3" Disc	 Mandrel
GRIT	055395-	055395-
50	63891	—
36	63890	—
24	63889	—
1/4" Mandrel	—	63893
<b>PKG/CASE</b>	<b>20/80</b>	<b>5/50</b>