

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : ACTIVATOR-INTERMIX 3:1 PRIMER B
Product code : FEB0180

1.2. Relevant identified uses of the substance or mixture and uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Endura Manufacturing Company Ltd.
12425 149 Street NW
Edmonton, T5L 2J6 - Canada
T 1-780-451-4242 - F 1-780-452-5079
info@endura.ca - www.endurapaint.com

1.4. Emergency telephone number

Emergency number : In the event of an emergency involving dangerous goods:
in Canada call CANUTEC at 613-996-6666 or *666 on a cellular phone.
in the US call CHEMTREC at 800-424-9300 (Account Name for US is Polyglass Coatings)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification


Flam. Liq. 2	H225 - Highly flammable liquid and vapor
Acute Tox. 4 (Inhalation:dust,mist)	H332 - Harmful if inhaled
Skin Irrit. 2	H315 - Causes skin irritation
Eye Dam. 1	H318 - Causes serious eye damage
Skin Sens. 1	H317 - May cause an allergic skin reaction
STOT SE 3	H336 - May cause drowsiness or dizziness
STOT RE 2	H373 - May cause damage to organs through prolonged or repeated exposure

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H225 - Highly flammable liquid and vapor
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H332 - Harmful if inhaled
H336 - May cause drowsiness or dizziness
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment
P241 - Use explosion-proof electrical/ventilating/lighting equipment
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing must not be allowed out of the workplace
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

ACTIVATOR-INTERMIX 3:1 PRIMER B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P302+P352 - IF ON SKIN: Wash with plenty of soap and water
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a poison center or doctor
P312 - Call a poison center/doctor/physician if you feel unwell
P314 - Get medical advice/attention if you feel unwell.
P321 - Specific treatment (see 4.1. First aid procedures on this label)
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P363 - Wash contaminated clothing before reuse.
P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO2) to extinguish
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container in accordance with all local, regional, national and international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
xylene, mixture of isomers	(CAS-No.) 1330-20-7	31.721	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315
toluene	(CAS-No.) 108-88-3	24.942	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
1-butanol	(CAS-No.) 71-36-3	5 – 10	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336 STOT SE 3, H335
benzyl alcohol	(CAS-No.) 100-51-6	< 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332
2,4,6-tris(dimethylaminomethyl)phenol	(CAS-No.) 90-72-2	< 5	Skin Irrit. 2, H315 Eye Irrit. 2, H319
triethylenetetramine	(CAS-No.) 112-24-3	< 5	Acute Tox. 3 (Dermal), H311 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412
tetraethylenepentamine	(CAS-No.) 112-57-2	< 5	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Skin Corr. 1A, H314 Skin Sens. 1, H317 Aquatic Chronic 2, H411

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: Call a poison center/doctor/physician if you feel unwell. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

ACTIVATOR-INTERMIX 3:1 PRIMER B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off all contaminated clothing immediately. If skin irritation or rash occurs: Get medical advice/attention. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Specific treatment (see 4.1. First aid procedures on this label). If skin irritation or rash occurs:
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately. Immediately call a poison center or doctor/physician.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell. Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. May cause an allergic skin reaction. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction. Causes skin irritation.
Symptoms/effects after eye contact	: Serious damage to eyes. Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapor.
Explosion hazard	: May form flammable/explosive vapor-air mixture.
Reactivity	: Highly flammable liquid and vapor.

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.
------------------	--

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes. Evacuate unnecessary personnel.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8 Exposure controls/personal protection". Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapors/spray.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
Other information	: Dispose of materials or solid residues at an authorized site.

ACTIVATOR-INTERMIX 3:1 PRIMER B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.4. Reference to other sections

For further information refer to section 8 : Exposure-controls/personal protection". See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Handle empty containers with care because residual vapors are flammable.
Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No naked lights. No smoking. Avoid breathing dust/fume/gas/mist/vapors/spray.
Hygiene measures	: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical/ventilating/lighting equipment.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. Keep only in the original container in a cool, well ventilated place away from : Keep in fireproof place.
Incompatible products	: Strong bases. strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight. Heat sources.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

xylene, mixture of isomers (1330-20-7)		
ACGIH	Remark (ACGIH)	URT & eye irr; CNS impair
OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	OSHA PEL (STEL) (mg/m ³)	655 mg/m ³

1-butanol (71-36-3)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr
OSHA	OSHA PEL (TWA) (mg/m ³)	300 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm

toluene (108-88-3)		
ACGIH	ACGIH TWA (ppm)	20 ppm (Toluene; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	Remark (ACGIH)	Visual impair; female repro;
OSHA	Remark (OSHA)	(2) See Table Z-2.

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Protective gloves. Wear protective gloves.
Eye protection	: Safety glasses. Chemical goggles or safety glasses.
Skin and body protection	: Wear suitable protective clothing.

ACTIVATOR-INTERMIX 3:1 PRIMER B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory protection	: Wear respiratory protection. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.
Environmental exposure controls	: Avoid release to the environment.
Other information	: When using, do not eat, drink or smoke.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
	: No data available
	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 100 °C 212 °F
Flash point	: 4.44 °C 40 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: 1.1 – 11.25 vol %
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 0.901 g/ml
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: 449 °C 840.2 °F
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

VOC content (Regulatory - Less water and exempt solvents)	: 667.39 g/l 5.569 lb/gal
VOC content (Material - Actual)	: 667.39 g/l 5.569 lb/gal
Percent Solids (Weight)	: 25.9 % (wt%)
Percent Solids (Volume)	: 23.651 %
Percent Volatile (Weight)	: 74.1 %
Percent Volatile (Volume)	: 76.349 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions. Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Not established.

ACTIVATOR-INTERMIX 3:1 PRIMER B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. Direct sunlight. Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

ACTIVATOR-INTERMIX 3:1 PRIMER B	
ATE US (dust, mist)	4.284 mg/l/4h
xylene, mixture of isomers (1330-20-7)	
LD50 oral rat	3523 – 8600 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; 3523 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value; >4000 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rabbit	> 4200 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	29 mg/l/4h (Rat; Experimental value; 27.57 mg/l/4h; Rat; Experimental value)
ATE US (oral)	3523 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (vapors)	29 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
1-butanol (71-36-3)	
LD50 oral rat	2292 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Female, Experimental value, Oral)
LD50 dermal rabbit	3430 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal)
ATE US (oral)	2292 mg/kg body weight
ATE US (dermal)	3430 mg/kg body weight
benzyl alcohol (100-51-6)	
LD50 oral rat	1620 mg/kg bw/day (Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg (EPA OTS 798.1100, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 inhalation rat (mg/l)	> 4.18 mg/l air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))
ATE US (oral)	1620 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
tetraethylenepentamine (112-57-2)	
LD50 oral rat	3990 mg/kg (Rat; Literature study; 3250 mg/kg bodyweight; Rat; Literature study)
LD50 dermal rabbit	660 mg/kg (Rabbit; Literature study; 660-1260 mg/kg bodyweight; Rabbit; Literature study)
ATE US (oral)	500 mg/kg body weight
ATE US (dermal)	660 mg/kg body weight
triethylenetetramine (112-24-3)	
LD50 oral rat	2500 mg/kg (Rat; Literature; 1716 mg/kg bodyweight; Rat; Literature)
LD50 dermal rabbit	805 mg/kg (Rabbit; Literature; 1465 mg/kg bodyweight; Rabbit; Literature)
ATE US (oral)	2500 mg/kg body weight
ATE US (dermal)	805 mg/kg body weight
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
LD50 oral rat	2169 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))

ACTIVATOR-INTERMIX 3:1 PRIMER B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
ATE US (oral)	2169 mg/kg body weight
toluene (108-88-3)	
LD50 oral rat	> 2000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; 5580 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	12223 mg/kg (Rabbit; Literature study; Other; >5000 mg/kg bodyweight; Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	> 20 mg/l/4h (Rat; Literature study)
ATE US (dermal)	12223 mg/kg body weight
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
xylene, mixture of isomers (1330-20-7)	
IARC group	3 - Not Classifiable

toluene (108-88-3)	
IARC group	3 - Not Classifiable
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: May cause drowsiness or dizziness.
Specific target organ toxicity – repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met. Harmful if inhaled.
Symptoms/effects after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. May cause an allergic skin reaction. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction. Causes skin irritation.
Symptoms/effects after eye contact	: Serious damage to eyes. Causes serious eye damage.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
-------------------	---

1-butanol (71-36-3)	
LC50 fish 1	1376 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Pimephales promelas, Static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	1328 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 (algae)	225 mg/l (OECD 201: Alga, Growth Inhibition Test, 96 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
benzyl alcohol (100-51-6)	
LC50 fish 1	460 mg/l (EPA OPP 72-1, 96 h, Pimephales promelas, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 Daphnia 1	230 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Fresh water, Experimental value, Locomotor effect)
ErC50 (algae)	770 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
tetraethylenepentamine (112-57-2)	
EC50 Daphnia 1	24.1 mg/l (EC50; EU Method C.2; 48 h; Daphnia magna; Static system)

ACTIVATOR-INTERMIX 3:1 PRIMER B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

tetraethylenepentamine (112-57-2)	
LC50 fish 2	420 mg/l (LC50; EU Method C.1; 96 h; Poecilia reticulata; Semi-static system; Fresh water; Experimental value)
Threshold limit algae 1	0.5 mg/l (NOEC; OECD 201: Alga, Growth Inhibition Test; 72 h; Selenastrum capricornutum)
Threshold limit algae 2	6.8 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Selenastrum capricornutum)
triethylenetetramine (112-24-3)	
EC50 Daphnia 1	311 mg/l (EC50; Equivalent or similar to OECD 202; 48 h; Daphnia magna)
LC50 fish 2	495 mg/l (LC50; 96 h; Pimephales promelas)
Threshold limit algae 1	≥ 100 mg/l (ErC50; DIN 38412-9; 72 h; Scenedesmus subspicatus)
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
LC50 fish 1	175 mg/l (APHA, 96 h, Cyprinus carpio, Static system, Fresh water, Experimental value, Nominal concentration)
ErC50 (algae)	84 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, GLP)

12.2. Persistence and degradability

ACTIVATOR-INTERMIX 3:1 PRIMER B	
Persistence and degradability	Not established.
xylene, mixture of isomers (1330-20-7)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the substance available. Photolysis in the air.
1-butanol (71-36-3)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.1 – 1.92 g O ₂ /g substance
Chemical oxygen demand (COD)	2.46 g O ₂ /g substance
ThOD	2.59 g O ₂ /g substance
BOD (% of ThOD)	0.33 – 0.79
benzyl alcohol (100-51-6)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.6 g O ₂ /g substance
Chemical oxygen demand (COD)	2.4 g O ₂ /g substance
ThOD	2.5 g O ₂ /g substance
tetraethylenepentamine (112-57-2)	
Persistence and degradability	Not readily biodegradable in water. Low potential for mobility in soil. Adsorbs into the soil.
triethylenetetramine (112-24-3)	
Persistence and degradability	Not readily biodegradable in water. No (test)data on mobility of the substance available. Photodegradation in the air.
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Persistence and degradability	Not readily biodegradable in water.
toluene (108-88-3)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	2.15 g O ₂ /g substance
Chemical oxygen demand (COD)	2.52 g O ₂ /g substance
ThOD	3.13 g O ₂ /g substance
BOD (% of ThOD)	0.69

12.3. Bioaccumulative potential

ACTIVATOR-INTERMIX 3:1 PRIMER B	
Bioaccumulative potential	Not established.
xylene, mixture of isomers (1330-20-7)	
BCF fish 2	7 – 26 (BCF; 8 weeks; Oncorhynchus mykiss; Flow-through system; Fresh water)
Partition coefficient n-octanol/water (Log Pow)	3.2 (Conclusion by analogy; 20 °C)

ACTIVATOR-INTERMIX 3:1 PRIMER B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

xylene, mixture of isomers (1330-20-7)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
1-butanol (71-36-3)	
BCF other aquatic organisms 1	3.162 l/kg (BCFBAF v3.01, Calculated value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	1 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
benzyl alcohol (100-51-6)	
Partition coefficient n-octanol/water (Log Pow)	1 – 1.1 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
tetraethylenepentamine (112-57-2)	
BCF other aquatic organisms 1	4.2 (BCF)
Partition coefficient n-octanol/water (Log Pow)	-3.16 (Calculated; EPIWIN)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
triethylenetetramine (112-24-3)	
Partition coefficient n-octanol/water (Log Pow)	-1.86 – -1.41 (Calculated)
Bioaccumulative potential	Bioaccumulation: not applicable.
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Partition coefficient n-octanol/water (Log Pow)	-0.66 (Experimental value, EPA OPPTS 830.7550: Partition Coefficient (n-octanol/water), Shake Flask Method, 21.5 °C)
Bioaccumulative potential	Not bioaccumulative.
toluene (108-88-3)	
BCF fish 2	90 (BCF; 72 h; Leuciscus idus; Static system; Fresh water)
Partition coefficient n-octanol/water (Log Pow)	2.73 (Experimental value; Other; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

xylene, mixture of isomers (1330-20-7)	
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.
1-butanol (71-36-3)	
Surface tension	69.9 mN/m (20 °C, 1 g/l, OECD 115: Surface Tension of Aqueous Solutions)
Partition coefficient n-octanol/water (Log Koc)	0.54 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil. May be harmful to plant growth, blooming and fruit formation.
benzyl alcohol (100-51-6)	
Surface tension	39 mN/m (20 °C)
Partition coefficient n-octanol/water (Log Koc)	1.122 – 1.332 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Ecology - soil	Highly mobile in soil.
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Partition coefficient n-octanol/water (Log Koc)	1.32 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.
toluene (108-88-3)	
Surface tension	0.03 N/m (20 °C)

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container in accordance with all local, regional, national and international regulations.
Additional information	: Flammable vapors may accumulate in the container. Handle empty containers with care because residual vapors are flammable.

ACTIVATOR-INTERMIX 3:1 PRIMER B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1263 Paint related material (including paint thinning, drying, removing, or reducing compound), 3, II

UN-No.(DOT) : UN1263

Proper Shipping Name (DOT) : Paint related material
including paint thinning, drying, removing, or reducing compound

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 173

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons).

B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).

TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Other information : No supplementary information available.

Transportation of Dangerous Goods

Transport document description : UN1263 PAINT RELATED MATERIAL (PAINT RELATED MATERIAL), 3, II

UN-No. (TDG) : UN1263

Proper Shipping Name (Transportation of Dangerous Goods) : PAINT RELATED MATERIAL

TDG Primary Hazard Classes : 3 - Class 3 - Flammable Liquids

Packing group : II - Medium Danger

TDG Special Provisions : 59 - Substances that are listed by name in Schedule 1 must not be transported under this shipping name. Substances transported under this shipping name may contain not more than 20 per cent nitrocellulose if the nitrocellulose contains not more than 12.6 per cent nitrogen (by dry mass), 83 - Repealed SOR/2014-152

ACTIVATOR-INTERMIX 3:1 PRIMER B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosive Limit and Limited Quantity Index : 5
Passenger Carrying Road Vehicle or Passenger : 5
Carrying Railway Vehicle Index

Transport by sea

Class (IMDG) : 3 - Flammable liquids
Packing group (IMDG) : II - substances presenting medium danger

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

xylene, mixture of isomers	CAS-No. 1330-20-7	31.721%
1-butanol	CAS-No. 71-36-3	5 – 10%
toluene	CAS-No. 108-88-3	24.942%

xylene, mixture of isomers (1330-20-7)

Listed on SARA Section 313 (Specific toxic chemical listings)

CERCLA RQ 100 lb

1-butanol (71-36-3)

Listed on SARA Section 313 (Specific toxic chemical listings)

CERCLA RQ 5000 lb

toluene (108-88-3)

Listed on SARA Section 313 (Specific toxic chemical listings)

CERCLA RQ 1000 lb

15.2. International regulations

CANADA

ACTIVATOR-INTERMIX 3:1 PRIMER B

Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

This product can expose you to toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

toluene (108-88-3)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	Yes	Yes	Yes	7000

ACTIVATOR-INTERMIX 3:1 PRIMER B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

xylene, mixture of isomers (1330-20-7)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

1-butanol (71-36-3)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

tetraethylenepentamine (112-57-2)

U.S. - New Jersey - Right to Know Hazardous Substance List

triethylenetetramine (112-24-3)

U.S. - New Jersey - Right to Know Hazardous Substance List

toluene (108-88-3)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Revision date : 11/23/2020
Other information : None.

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

SDS US Endura

The information contained here has been compiled from sources considered by Endura Manufacturing Co. Ltd to be dependable and is accurate to the best of the Company's knowledge. However, neither Endura Manufacturing Co. Ltd or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.