



## Technical Data Sheet

# Automotive Art Matting Agent 20-55



### General Information:

Automotive Art Matting Agent 20-55 is used to matt any Automotive Art's 2:1 Clear Coats or Motocryl paint, allowing for either a full or semi matt finish. Furthermore, painters can easily create matt finishes without having to purchase additional specialized paints.

### Mixing Ratio:



**Add up to 40% by vol. to uncatalyzed AART/Toucan:**

- Clearcoats
- Motocryl
- 2K Converter (Single-Stage)

<u>Vol.</u>	<u>Degree of Gloss</u>
20%	Semi-Gloss
30%	Satin Gloss
40%	Matt

### Packing & Shelf Life:

**Sizes:** 1L  
**Shelf life:** Under normal storage conditions two years (unopened tins).

### Notes:

- Never add to Motobase 80 Line or 8LV Line
- Additive should be added before hardener
- Product mixing ratio remains the same after adding 20-55

### Technical Data:

Volume Ratio	
Specific Gravity:	1.016 kg/l
Flash Point:	24°C, (76°F)
Solids Vol %:	NA
Solids Wt. %:	NA
Coverage:	NA
Viscosity DINCUP 4mm/20°C :	NA
Gloss:	Matt
Color:	Milky
V.O.C. Actual:	579 g/l (4.8 lbs/gal)
V.O.C. Regulatory RTS (less water, less exempts):	579 g/l (4.8 lbs/gal)
Applicable Use Category:	Ancillaries

See Material Safety Data Sheet and Labels for additional Safety Information and handing instructions.