

Revision date: 2018/11/02 Page: 1/10
Version: 4.2 (30507002/SDS GEN CA/EN)

1. Identification

Product identifier used on the label

LA1291 Low Strght Helio Blue

Recommended use of the chemical and restriction on use

Recommended use*: for industrial use only

Details of the supplier of the safety data sheet

Company:

BASF Canada Inc. 100 Milverton Drive Mississauga, ON L5R 4H1, CANADA

Telephone: +1 289 360-1300

Emergency telephone number

CANUTEC (reverse charges): (613) 996-6666 BASF HOTLINE: (800) 454-COPE (2673)

Other means of identification

Chemical family: Coating

2. Hazards Identification

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

Classification of the product

Skin Corr./Irrit. 2 Skin corrosion/irritation

Eye Dam./Irrit. 2B Serious eye damage/eye irritation

Skin Sens. 1 Skin sensitization Carc. 2 Carcinogenicity

STOT SE 3 (irritating to Specific target organ toxicity — single exposure

respiratory system)

Flam. Liq. 2 Flammable liquids

Aquatic Acute 2 Hazardous to the aquatic environment - acute Aquatic Chronic 3 Hazardous to the aquatic environment - chronic

^{*} The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Revision date: 2018/11/02 Page: 2/10 Version: 4.2 (30507002/SDS GEN CA/EN)

STOT RE

Specific target organ toxicity — repeated exposure

Label elements

Pictogram:



Signal Word: Danger

Hazard Statement:

H320 Causes eye irritation. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

2

H412 Harmful to aquatic life with long lasting effects.

H401 Toxic to aquatic life.

H225 Highly flammable liquid and vapour.

H373 May cause damage to organs (Auditory organ) through prolonged or

repeated exposure.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

Precautionary Statements (Prevention):

P280 Wear protective gloves/protective clothing/eye protection/face

protection.

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P264 Wash with plenty of water and soap thoroughly after handling.

P281 Use personal protective equipment as required. P271 Use only outdoors or in a well-ventilated area.

P242 Use only non-sparking tools.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P243 Take action to prevent static discharges.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P202 Do not handle until all safety precautions have been read and

understood.

P260 Do not breathe dust or mist.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P201 Obtain special instructions before use.

Precautionary Statements (Response):

Revision date : 2018/11/02	Page: 3/10
Version: 4.2	(30507002/SDS GEN CA/EN)

P312 P305 + P351 + P338	Call a POISON CENTER or doctor/physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P370 + P378	In case of fire: Use water spray for extinction.
P363	Wash contaminated clothing before reuse.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P321	Specific treatment (see on this label).
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.

Precautionary Statements (Storage):

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Precautionary Statements (Disposal):

P501 Dispose of contents/container to hazardous or special waste collection

point.

Hazards not otherwise classified

No applicable information available.

3. Composition / Information on Ingredients

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

CAS Number	Weight %	Chemical name
96-29-7	>= 0.2 - < 0.3%	butanone oxime
100-41-4	>= 5.0 - < 7.0%	ethylbenzene
123-86-4	>= 10.0 - < 15.0%	n-Butyl acetate
1330-20-7	>= 25.0 - < 50.0%	Xylene
64742-95-6	>= 1.0 - < 3.0%	Solvent naphtha (petroleum), light arom.

4. First-Aid Measures

Description of first aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

If on skin:

Immediately wash thoroughly with soap and water, seek medical attention.

Revision date: 2018/11/02 Page: 4/10 Version: 4.2 (30507002/SDS GEN CA/EN)

If in eyes:

Flush with copious amounts of water for at least 15 minutes. Hold eyelids open to facilitate rinsing. If irritation develops, seek medical attention. Seek medical attention.

If swallowed:

Immediate medical attention required. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Do not induce vomiting. Rinse mouth and then drink 200-300 ml of water.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no

known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media: carbon dioxide, foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons: water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

Vapors and/or decomposition products are irritant and/or toxic. If product is heated above decomposition temperature acrid smoke and fumes will be released.

Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Notify proper authorities. Do not flood burning material with water due to potential spreading of fire. Flash fire may occur. Run-off water from fire may cause pollution. Contain contaminated water/firefighting water. Remove product from areas of fire, or otherwise cool sealed containers with water in order to avoid pressure build up due to heat. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Use antistatic tools. Extinguish sources of ignition nearby and downwind. Avoid prolonged inhalation. Wear suitable personal protective clothing and equipment. Ensure adequate ventilation.

Revision date: 2018/11/02 Page: 5/10 Version: 4.2 (30507002/SDS GEN CA/EN)

Environmental precautions

Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

Dike spillage. Spills should be contained, solidified, and placed in suitable containers for disposal. Place into appropriately labeled waste containers.

7. Handling and Storage

Precautions for safe handling

Handle and open container with care. WARNING: Empty containers may still contain hazardous residue. Use static lines when mixing and transferring material. Do not puncture, drop, or slide containers. Ensure adequate ventilation. Avoid contact with the skin, eyes and clothing.

Protection against fire and explosion:

Risk of explosion if heated under confinement. Use antistatic tools. Exhaust fans should be explosion proof. Avoid all sources of ignition: heat, sparks, open flame. Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources. Sealed containers should be protected against heat as this results in pressure build-up.

Conditions for safe storage, including any incompatibilities

Segregate from strong bases. Segregate from oxidizing agents. Segregate from incompatible substances. Segregate from strong acids.

Suitable materials for containers: Carbon steel (Iron), tinned carbon steel (Tinplate)

Further information on storage conditions: Keep container tightly closed. Protect from direct sunlight.

Storage stability:

Consult local fire marshal for storage requirements.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

ethylbenzene	OSHA PEL	PEL 100 ppm 435 mg/m3; TWA value 100 ppm 435 mg/m3; STEL value 125 ppm 545 mg/m3;
	ACGIH TLV	TWA value 20 ppm ;
n-Butyl acetate	OSHA PEL	PEL 150 ppm 710 mg/m3; STEL value 200 ppm 950 mg/m3; TWA value 150 ppm 710 mg/m3;
	ACGIH TLV	STEL value 150 ppm; TWA value 50 ppm;
Xylene	OSHA PEL	PEL 100 ppm 435 mg/m3; TWA value 100 ppm 435 mg/m3; STEL value 150 ppm 655 mg/m3;
	ACGIH TLV	TWA value 100 ppm; STEL value 150 ppm;

Revision date: 2018/11/02 Page: 6/10 Version: 4.2 (30507002/SDS GEN CA/EN)

Personal protective equipment

Respiratory protection:

Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination. Wear a NIOSH-certified (or equivalent) organic vapour respirator. Particulate filters should be added during spray operations. Wear respiratory protection if ventilation is inadequate.

Hand protection:

Chemical resistant protective gloves

Eye protection:

Wear face shield if splashing hazard exists. Tightly fitting safety goggles (chemical goggles).

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Work place should be equipped with a shower and an eye wash. Remove contaminated clothing. Remove contaminated clothing immediately and clean before re-use or dispose it if necessary. Contact lenses should not be worn. Hands and/or face should be washed before breaks and at the end of the shift.

(ASTM D3278)

(calculated)

9. Physical and Chemical Properties

Form: liquid

Odour: product specific

Odour threshold: No applicable information available.

Colour: blue

pH value:

Melting point:

No applicable information available.

No applicable information available.

No applicable information available.

Sublimation point:

No applicable information available.

No applicable information available.

Flash point: 9.00 °C

Flammability: No applicable information available. Lower explosion limit: No applicable information available.

Upper explosion limit:

Autoignition:

Vapour pressure:

No applicable information available.

No applicable information available.

No applicable information available.

No applicable information available.

Density: 0.9789 g/cm3

(20 °C)

Relative density: 0.9790

(20°C)

Vapour density: No applicable information available. Partitioning coefficient n- No applicable information available.

octanol/water (log Pow):

Thermal decomposition: No applicable information available. Viscosity, dynamic: No applicable information available.

Viscosity, kinematic: 411.600 mm2/s

Solubility in water:
Solubility (quantitative):
Solubility (qualitative):
No applicable information available.
No applicable information available.
No applicable information available.
No applicable information available.

10. Stability and Reactivity

Reactivity

No applicable information available.

Revision date: 2018/11/02 Page: 7/10 Version: 4.2 (30507002/SDS GEN CA/EN)

Chemical stability

The product is chemically stable.

Possibility of hazardous reactions

No applicable information available.

Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge.

Incompatible materials

strong oxidizing agents, strong bases, strong acids

Hazardous decomposition products

Decomposition products: carbon dioxide, carbon monoxide

Thermal decomposition:

No applicable information available.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Primary routes of entry

Solvents are absorbed through the skin.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact.

Information on: butanone oxime

Assessment of acute toxicity:Of moderate toxicity after short-term skin contact. In animal studies the substance is virtually nontoxic after a single ingestion. The inhalation of a highly enriched/saturated vapor-air-mixture represents an unlikely acute hazard.

Information on: ethylbenzene

Assessment of acute toxicity:Of moderate toxicity after short-term inhalation. Virtually nontoxic after a single skin contact. Of low toxicity after single ingestion.

Information on: Solvent naphtha (petroleum), light arom.

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. No deaths at the highest dose tested after short-term inhalation. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. Of low toxicity after short-term skin contact.

Oral

No applicable information available.

Revision date : 2018/11/02 Page: 8/10 Version: 4.2 (30507002/SDS GEN CA/EN)

Inhalation

No applicable information available.

Dermal

No applicable information available.

Assessment other acute effects

Assessment of STOT single:

Causes temporary irritation of the respiratory tract.

Irritation / corrosion

Assessment of irritating effects: Skin contact causes irritation.

Information on: butanone oxime

Assessment of irritating effects: May cause severe damage to the eyes. Not irritating to the skin.

Information on: ethylbenzene

Assessment of irritating effects: May cause slight irritation to the skin. May cause slight irritation to

the eyes.

Information on: Xylene

Assessment of irritating effects: Skin contact causes irritation. Eye contact causes irritation.

Information on: Solvent naphtha (petroleum), light arom.

Assessment of irritating effects: May cause slight irritation to the skin. May cause slight irritation to

the eyes. The product has not been tested. The statement has been derived from

substances/products of a similar structure or composition.

Sensitization

Information on: butanone oxime Assessment of sensitization:

Sensitization after skin contact possible.

Aspiration Hazard

No applicable information available.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure may affect certain organs.

Information on: butanone oxime

Information on: ethylbenzene

Assessment of repeated dose toxicity: The substance may cause damage to the liver after repeated ingestion of high doses, as shown in animal studies. The substance may cause deafness after repeated inhalation. The substance may cause deafness after repeated ingestion.

.....

Carcinogenicity

Assessment of carcinogenicity: Contains a suspect carcinogen.

Information on: ethylbenzene

Revision date: 2018/11/02 Page: 9/10 Version: 4.2 (30507002/SDS_GEN_CA/EN)

Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. The effect is caused by an animal specific mechanism that has no human counter part. A clear indication of an increased risk of cancer in humans has so far not been shown. IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).

·-----

Teratogenicity

Information on: Xylene

Assessment of teratogenicity: In animal studies the substance did not cause malformations.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

12. Ecological Information

No applicable information available.

13. Disposal considerations

Waste disposal of substance:

Do not incinerate closed containers. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. Do not discharge into drains/surface waters/groundwater.

Must be disposed of or incinerated in accordance with local regulations.

Container disposal:

Do not reuse containers without commercial reconditioning.

14. Transport Information

Land transport

TDG

Hazard class: 3 Packing group: II

ID number: UN 1263

Hazard label: 3
Proper shipping name: PAINT

Sea transport

IMDG

Hazard class: 3 Packing group: II

ID number: UN 1263 Hazard label: 3

Marine pollutant:

Revision date: 2018/11/02 Page: 10/10 Version: 4.2 (30507002/SDS GEN CA/EN)

Proper shipping name: PAINT

Air transport IATA/ICAO

Hazard class: 3 Packing group: II

ID number: UN 1263

Hazard label: 3

Proper shipping name: PAINT

15. Regulatory Information

Federal Regulations

Registration status:

Chemical DSL, CA released / listed

NFPA Hazard codes:

Health: 2 Fire: 3 Reactivity: 0 Special:

16. Other Information

SDS Prepared by:

BASF NA Product Regulations SDS Prepared on: 2018/11/02

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

END OF DATA SHEET