

Revision date: 2019/01/16 Page: 1/10
Version: 5.0 (30717091/SDS GEN US/EN)

#### 1. Identification

#### Product identifier used on the label

# 910 Universal PrepCleaner

### Recommended use of the chemical and restriction on use

Recommended use\*: for industrial use only

### Details of the supplier of the safety data sheet

Company:

BASF CORPORATION 100 Park Avenue Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

## **Emergency telephone number**

CHEMTREC: 1-800-424-9300

BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

#### 2. Hazards Identification

## According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

# Classification of the product

Skin Corr./Irrit. 2 Skin corrosion/irritation

Eye Dam./Irrit. 2A Serious eye damage/eye irritation

Flam. Liq. 2 Flammable liquids

#### Label elements

Pictogram:

<sup>\*</sup> The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Revision date: 2019/01/16 Page: 2/10 Version: 5.0 (30717091/SDS GEN US/EN)



Signal Word: Danger

Hazard Statement:

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Precautionary Statements (Prevention):

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face

protection.

P240 Ground and bond container and receiving equipment.

P233 Keep container tightly closed.

P243 Take action to prevent static discharges.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P264 Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention. P332 + P313 If skin irritation occurs: Get medical advice/attention.

P321 Specific treatment (see on this label).

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use water spray for extinction.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

Precautionary Statements (Storage):

P403 + P235 Store in a well-ventilated place. Keep cool.

Precautionary Statements (Disposal):

P501 Dispose of contents/container to hazardous or special waste collection

point.

#### Hazards not otherwise classified

No applicable information available.

## 3. Composition / Information on Ingredients

# According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

| CAS Number | <u>Weight %</u>  | Chemical name             |
|------------|------------------|---------------------------|
| 67-64-1    | >= 7.0 - < 10.0% | Acetone                   |
| 2807-30-9  | >= 1.0 - < 3.0%  | Ethanol, 2-propoxy-       |
| 68439-46-3 | >= 0.3 - < 1.0%  | alcohol(C9-C11)ethoxilate |

Revision date: 2019/01/16 Page: 3/10 Version: 5.0 (30717091/SDS GEN US/EN)

#### 4. First-Aid Measures

# **Description of first aid measures**

#### General advice:

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove contaminated clothing.

#### If inhaled:

Keep patient calm, remove to fresh air. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

#### If on skin:

If irritation develops, seek medical attention. Wash affected areas with water for at least 15 minutes.

#### If in eyes:

Flush with copious amounts of water for at least 15 minutes. Hold eyelids open to facilitate rinsing. If irritation develops, seek medical attention. Seek medical attention.

#### If swallowed:

Immediate medical attention required. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Do not induce vomiting. Rinse mouth and then drink 200-300 ml of water.

## Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

## Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

## 5. Fire-Fighting Measures

# **Extinguishing media**

Suitable extinguishing media: carbon dioxide, foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons: water jet

#### Special hazards arising from the substance or mixture

Hazards during fire-fighting:

Vapors and/or decomposition products are irritant and/or toxic. If product is heated above decomposition temperature acrid smoke and fumes will be released.

### Advice for fire-fighters

Revision date: 2019/01/16 Page: 4/10 Version: 5.0 (30717091/SDS\_GEN\_US/EN)

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

#### **Further information:**

Notify proper authorities. Do not flood burning material with water due to potential spreading of fire. Flash fire may occur. Run-off water from fire may cause pollution. Contain contaminated water/firefighting water. Remove product from areas of fire, or otherwise cool sealed containers with water in order to avoid pressure build up due to heat. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

#### 6. Accidental release measures

## Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Use antistatic tools. Extinguish sources of ignition nearby and downwind. Avoid prolonged inhalation. Wear suitable personal protective clothing and equipment. Ensure adequate ventilation.

## **Environmental precautions**

Do not discharge into drains/surface waters/groundwater.

A spill of or in excess of the reportable quantity requires notification to state, local and national emergency authorities.

#### Methods and material for containment and cleaning up

Dike spillage. Spills should be contained, solidified, and placed in suitable containers for disposal. Place into appropriately labeled waste containers.

## 7. Handling and Storage

## Precautions for safe handling

Handle and open container with care. WARNING: Empty containers may still contain hazardous residue. Use static lines when mixing and transferring material. Do not puncture, drop, or slide containers. Ensure adequate ventilation. Avoid contact with the skin, eyes and clothing.

Proper ventilation and respiratory protection is required when sanding, flame cutting, welding or brazing coated surfaces. Do not apply to hot surfaces.

Protection against fire and explosion:

Risk of explosion if heated under confinement. Use antistatic tools. Exhaust fans should be explosion proof. Avoid all sources of ignition: heat, sparks, open flame. Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources. Sealed containers should be protected against heat as this results in pressure build-up.

#### Conditions for safe storage, including any incompatibilities

Segregate from strong bases. Segregate from oxidizing agents. Segregate from incompatible substances. Segregate from strong acids.

Suitable materials for containers: Carbon steel (Iron), tinned carbon steel (Tinplate), Stove-lacquer KNS L-5X, Stove-lacquer Valspar HXR008F red, HDPE fluorinated

Further information on storage conditions: Keep container tightly closed. Store protected against freezing. Protect from direct sunlight.

Storage stability:

Revision date: 2019/01/16 Page: 5/10 Version: 5.0 (30717091/SDS GEN US/EN)

Consult local fire marshal for storage requirements.

Protect from temperatures above: 49 °C

# 8. Exposure Controls/Personal Protection

### Components with occupational exposure limits

Acetone OSHA PEL PEL 1,000 ppm 2,400 mg/m3 ; STEL value

1,000 ppm 2,400 mg/m3; TWA value 750 ppm

1,800 mg/m3;

ACGIH TLV TWA value 250 ppm; STEL value 500 ppm;

# Advice on system design:

General mechanical ventilation should comply with OSHA 1910.94. Provide local exhaust ventilation to maintain recommended P.E.L.

### Personal protective equipment

### Respiratory protection:

Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination. Wear a NIOSH-certified (or equivalent) organic vapour respirator. Particulate filters should be added during spray operations. Wear respiratory protection if ventilation is inadequate.

Observe OSHA regulations for respirator use (29 CFR 1910.134).

#### Hand protection:

Use appropriate chemically resistant gloves as determined by an evaluation of glove performance characteristics and the hazards and potential hazards identified, including but not limited to butyl, natural and synthetic rubber, nitrile, or neoprene.

#### Eye protection:

Wear face shield if splashing hazard exists. Tightly fitting safety goggles (chemical goggles).

#### **Body protection:**

Body protection must be chosen based on level of activity and exposure.

### General safety and hygiene measures:

Work place should be equipped with a shower and an eye wash. Remove contaminated clothing. Remove contaminated clothing immediately and clean before re-use or dispose it if necessary. Contact lenses should not be worn. Hands and/or face should be washed before breaks and at the end of the shift.

## 9. Physical and Chemical Properties

Form: liquid

Odour: of the solvent contained in the product Odour threshold: No applicable information available.

Colour: water white

pH value: No applicable information available. Melting point: No applicable information available.

Boiling range: 56.00 - 204.00 °C

132.80 - 399.20 °F

Sublimation point: No applicable information available.

Flash point: 18.89 °C (ASTM D3278) 66.00 °F (ASTM D3278)

Flammability: No applicable information available.

Revision date: 2019/01/16 Page: 6/10 Version: 5.0 (30717091/SDS GEN US/EN)

Lower explosion limit: 1.30 %(V) Upper explosion limit: 15.80 %(V)

Autoignition: No applicable information available. Vapour pressure: No applicable information available.

Density: 0.9748 g/cm3 (calculated)

(20 °C)

8.1354 lb/USg (calculated)

Relative density: 0.9748

( 20 °C)

Vapour density: No applicable information available. Partitioning coefficient n- No applicable information available.

octanol/water (log Pow):

Thermal decomposition: No applicable information available. Viscosity, dynamic: No applicable information available.

Viscosity, kinematic: < 20.500 mm2/s

Solubility in water:
Solubility (quantitative):
Solubility (qualitative):
Molar mass:
No applicable information available.
No applicable information available.
No applicable information available.
Evaporation rate:
No applicable information available.

# 10. Stability and Reactivity

## Reactivity

No applicable information available.

#### Chemical stability

The product is chemically stable.

#### Possibility of hazardous reactions

No applicable information available.

#### Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge.

## Incompatible materials

strong oxidizing agents, strong bases, strong acids

# Hazardous decomposition products

Decomposition products:

carbon dioxide, carbon monoxide

Thermal decomposition:

No applicable information available.

# 11. Toxicological information

## Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

#### **Acute Toxicity/Effects**

Revision date: 2019/01/16 Page: 7/10
Version: 5.0 (30717091/SDS\_GEN\_US/EN)

#### Acute toxicity

Assessment of acute toxicity: The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: Acetone

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact. High concentrations in the air may cause narcosis.

Information on: Ethanol, 2-propoxy-

Assessment of acute toxicity:Of moderate toxicity after short-term skin contact. The inhalation of a highly enriched/saturated vapor-air-mixture represents a potential acute hazard. Of low toxicity after single ingestion.

Information on: alcohol(C9-C11)ethoxilate

-----

#### Assessment other acute effects

No applicable information available.

#### Irritation / corrosion

Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.

Information on: Acetone

Assessment of irritating effects: Not irritating to the skin. Irritating to eyes.

Information on: Ethanol, 2-propoxy-

Assessment of irritating effects: Skin contact causes irritation. May cause severe damage to the

eyes.

Information on: alcohol(C9-C11)ethoxilate

,

#### Sensitization

Assessment of sensitization: No applicable information available.

#### Aspiration Hazard

No applicable information available.

# **Chronic Toxicity/Effects**

#### Repeated dose toxicity

Assessment of repeated dose toxicity: The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: Acetone

Assessment of repeated dose toxicity: The substance may cause damage to the testes after repeated ingestion of high doses, as shown in animal studies. The substance may cause damage to the hematological system after repeated ingestion of high doses. The substance may cause damage to the kidney after repeated ingestion of high doses, as shown in animal studies.

Information on: alcohol(C9-C11)ethoxilate

-----

#### Genetic toxicity

Assessment of mutagenicity: No applicable information available.

Revision date: 2019/01/16 Page: 8/10 Version: 5.0 (30717091/SDS GEN US/EN)

#### Carcinogenicity

Assessment of carcinogenicity: No applicable information available.

#### Reproductive toxicity

Assessment of reproduction toxicity: The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: Acetone

Assessment of reproduction toxicity: As shown in animal studies, the product may cause damage to the testes after repeated high exposures that cause other toxic effects.

\_\_\_\_\_

### **Teratogenicity**

Assessment of teratogenicity: No applicable information available.

## **Symptoms of Exposure**

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

## 12. Ecological Information

No applicable information available.

# 13. Disposal considerations

### Waste disposal of substance:

Do not incinerate closed containers. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. Do not discharge into drains/surface waters/groundwater.

Incinerate or dispose of in a RCRA-licensed facility. Dispose of in accordance with national, state and local regulations. It is the waste generator's responsibility to determine if a particular waste is hazardous under RCRA.

### Container disposal:

WARNING: Empty containers may still contain hazardous residue. Dispose of in accordance with national, state and local regulations.

# 14. Transport Information

### Land transport

**USDOT** 

Hazard class: 3 Packing group: II

ID number: UN 1263

Hazard label: 3

Proper shipping name: PAINT RELATED MATERIAL

## Sea transport

**IMDG** 

Hazard class: 3 Packing group: II

ID number: UN 1263

Revision date: 2019/01/16 Page: 9/10 Version: 5.0 (30717091/SDS GEN US/EN)

Hazard label: 3
Marine pollutant: NO

Proper shipping name: PAINT RELATED MATERIAL

Air transport IATA/ICAO

Hazard class: 3 Packing group: II

ID number: UN 1263

Hazard label: 3

Proper shipping name: PAINT RELATED MATERIAL

## 15. Regulatory Information

### **Federal Regulations**

Registration status:

Chemical TSCA, US released / listed

**EPCRA 311/312 (Hazard categories):** Refer to SDS section 2 for GHS hazard classes applicable for this product.

**EPCRA 313:** 

State regulations

State RTK CAS Number Chemical name

NJ 67-64-1 Acetone

2807-30-9 Ethanol, 2-propoxy-

PA 67-64-1 Acetone

2807-30-9 Ethanol, 2-propoxy-

**NFPA Hazard codes:** 

Health: 2 Fire: 3 Reactivity: 0 Special:

**HMIS III rating** 

Health: 2¤ Flammability: 3 Physical hazard:0

#### 16. Other Information

### SDS Prepared by:

BASF NA Product Regulations SDS Prepared on: 2019/01/16

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Revision date: 2019/01/16 Page: 10/10 Version: 5.0 (30717091/SDS GEN US/EN)

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK. **END OF DATA SHEET**