



We create chemistry

# Safety Data Sheet

## DH105 HI TEMP LV HRDNR

Revision date : 2020/07/24  
Version: 5.0

Page: 1/9  
(30112193/SDS\_GEN\_CA/EN)

### 1. Identification

#### Product identifier used on the label

**DH105 HI TEMP LV HRDNR**

#### Recommended use of the chemical and restriction on use

Recommended use\*: Paints, Coatings and Related Materials; for industrial use only

Unsuitable for use: Not intended for sale to or use by the general public.

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

#### Details of the supplier of the safety data sheet

##### Company:

BASF Canada Inc.  
100 Milverton Drive  
Mississauga, ON L5R 4H1, CANADA

Telephone: +1 289 360-1300

#### Emergency telephone number

CHEMTREC: 1-800-424-9300  
BASF HOTLINE: (800) 454-COPE (2673)

#### Other means of identification

Chemical family: Coating  
Synonyms: PAINT RELATED MATERIAL

### 2. Hazards Identification

#### According to Hazardous Products Regulations (HPR) (SOR/2015-17)

##### Classification of the product

Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
Skin Sens.	1	Skin sensitization
STOT SE	3 (irritating to respiratory system)	Specific target organ toxicity — single exposure
Flam. Liq.	3	Flammable liquids

# Safety Data Sheet

## DH105 HI TEMP LV HRDNR

Revision date : 2020/07/24  
Version: 5.0

Page: 2/9  
(30112193/SDS\_GEN\_CA/EN)

### Label elements

Pictogram:



Signal Word:  
Warning

Hazard Statement:

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash contaminated body parts thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P242	Use only non-sparking tools.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P243	Take action to prevent static discharges.
P233	Keep container tightly closed.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground and bond container and receiving equipment.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements (Response):

P312	Call a POISON CENTER or physician if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P370 + P378	In case of fire: Use water spray for extinction.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P333 + P313	If skin irritation or rash occurs: Get medical attention.
P303 + P361 + P353	IF ON SKIN (or hair): Remove or Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P337 + P313	If eye irritation persists: Get medical attention.

Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

**Hazards not otherwise classified**

# Safety Data Sheet

## DH105 HI TEMP LV HRDNR

Revision date : 2020/07/24  
Version: 5.0

Page: 3/9  
(30112193/SDS\_GEN\_CA/EN)

No applicable information available.

### 3. Composition / Information on Ingredients

#### According to Hazardous Products Regulations (HPR) (SOR/2015-17)

Hexane, 1,6-diisocyanato-, homopolymer

CAS Number: 28182-81-2

Content (W/W):  $\geq 25.0$  -  $< 50.0\%$

Synonym: 1,6-Diisocyanatohexane homopolymer

(OLIGOMER) Hexamethylene diisocyanate isocyanurate-type oligomers

CAS Number: 28182-81-2

Content (W/W):  $\geq 25.0$  -  $< 50.0\%$

Synonym: No data available.

4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene

CAS Number: 98-56-6

Content (W/W):  $\geq 25.0$  -  $< 50.0\%$

Synonym: No data available.

### 4. First-Aid Measures

#### Description of first aid measures

##### General advice:

Remove contaminated clothing.

##### If inhaled:

Keep patient calm, remove to fresh air. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

##### If in eyes:

Flush with copious amounts of water for at least 15 minutes. Hold eyelids open to facilitate rinsing. If irritation develops, seek medical attention. Seek medical attention.

#### Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

*Information on: 4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene*

*Symptoms: Overexposure may cause: lethargy, nausea, headache, dizziness*

#### Indication of any immediate medical attention and special treatment needed

##### Note to physician

Treatment:

Treat according to symptoms (decontamination, vital functions), no known specific antidote.

# Safety Data Sheet

## DH105 HI TEMP LV HRDNR

Revision date : 2020/07/24

Version: 5.0

Page: 4/9

(30112193/SDS\_GEN\_CA/EN)

### 5. Fire-Fighting Measures

#### Extinguishing media

Suitable extinguishing media:  
carbon dioxide, foam, dry powder

Unsuitable extinguishing media for safety reasons:  
water jet

#### Special hazards arising from the substance or mixture

##### Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

##### Further information:

Avoid water contamination in closed containers of confined areas, because carbon dioxide gas is generated. Remove product from areas of fire, or otherwise cool sealed containers with water in order to avoid pressure build up due to heat.

### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Wear suitable personal protective clothing and equipment. Ensure adequate ventilation.

#### Environmental precautions

Do not discharge into drains/surface waters/groundwater.

#### Methods and material for containment and cleaning up

Dike spillage. Wash down spill area with decontamination solution. Spill area can be decontaminated with the following recommended decontamination solution: Allow solution to stand for at least 10 minutes. Remove containers to a safe place, cover loosely, and allow to stand for 24 to 48 hours before sealing and disposing. Shovel into open container. Add additional decontamination solution to waste container. Mixture of 80 % water and 20 % non-ionic surfactant, or 90 - 95 % water, 3 - 8 % concentrated ammonia and 2 % detergent.

### 7. Handling and Storage

#### Precautions for safe handling

Handle and open container with care. Avoid water contamination in closed containers of confined areas, because carbon dioxide gas is generated. If bulging of drum occurs, transfer to well ventilated area, puncture to relieve pressure, open vent and let stand for 48 hours before resealing. Do not reseal container if contamination of the product is suspected. Use static lines when mixing and transferring material. Do not puncture, drop, or slide containers. Store in a well-ventilated place. Keep cool. Ensure adequate ventilation. Avoid contact with the skin, eyes and clothing.

Protection against fire and explosion:

Use antistatic tools. Exhaust fans should be explosion proof. Avoid all sources of ignition: heat, sparks, open flame. Sealed containers should be protected against heat as this results in pressure build-up.

#### Conditions for safe storage, including any incompatibilities

Segregate from oxidizing agents. Segregate from incompatible substances. Keep away from water.

# Safety Data Sheet

## DH105 HI TEMP LV HRDNR

Revision date : 2020/07/24  
Version: 5.0

Page: 5/9  
(30112193/SDS\_GEN\_CA/EN)

Further information on storage conditions: Protect against moisture. Carbon dioxide gas can cause containers to expand and possibly rupture explosively. Protect from direct sunlight. If moisture enters isocyanate containers, CO<sub>2</sub> forms and pressure builds up.

Storage stability:  
Slow non-hazardous polymerization possible when at or exceeding maximum temperatures.

### 8. Exposure Controls/Personal Protection

No occupational exposure limits known.

#### Personal protective equipment

##### **Respiratory protection:**

Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination.

##### **Hand protection:**

Use appropriate chemically impervious gloves as determined by an evaluation of glove performance characteristics and the hazards and potential hazards identified, including but not limited to butyl, natural and synthetic rubber, nitrile, or neoprene.

##### **Eye protection:**

Wear face shield if splashing hazard exists. Tightly fitting safety goggles (chemical goggles).

##### **Body protection:**

Body protection must be chosen based on level of activity and exposure.

##### **General safety and hygiene measures:**

Work place should be equipped with a shower and an eye wash. Remove contaminated clothing. Remove contaminated clothing immediately and clean before re-use or dispose it if necessary. Contact lenses should not be worn. Hands and/or face should be washed before breaks and at the end of the shift.

### 9. Physical and Chemical Properties

Form:	liquid	
Odour:	moderate odour	
Odour threshold:	No applicable information available.	
Colour:	clear	
pH value:	No applicable information available.	
Melting point:	No applicable information available.	
Freezing point:	No applicable information available.	
Boiling range:	138.60 - 355.00 °C	
Sublimation point:	No applicable information available.	
Flash point:	42 °C	
Flammability:	No applicable information available.	
Lower explosion limit:	0.90 %(V)	
Upper explosion limit:	10.50 %(V)	
Autoignition:	No applicable information available.	
Vapour pressure:	No applicable information available.	
Density:	1.2297 g/cm <sup>3</sup> ( 20 °C)	(calculated)
Relative density:	1.2297 ( 20 °C)	

# Safety Data Sheet

## DH105 HI TEMP LV HRDNR

Revision date : 2020/07/24  
Version: 5.0

Page: 6/9  
(30112193/SDS\_GEN\_CA/EN)

Vapour density:	No applicable information available.
Partitioning coefficient n-octanol/water (log Pow):	No applicable information available.
Thermal decomposition:	No applicable information available.
Viscosity, dynamic:	No applicable information available.
Viscosity, kinematic:	No applicable information available.
Solubility in water:	No applicable information available.
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.
Molar mass:	No applicable information available.
Evaporation rate:	No applicable information available.

## 10. Stability and Reactivity

### Reactivity

No applicable information available.

### Chemical stability

### Possibility of hazardous reactions

On contact with water, gaseous decomposition products are formed, which cause build-up of pressure in tightly closed containers. Reacts with water.

### Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid direct contact with water. Avoid electrostatic discharge.

### Incompatible materials

strong oxidizing agents, thiols, transition metal salts, water, amines, alcohols

### Hazardous decomposition products

Decomposition products:  
nitrogen oxides

Thermal decomposition:  
No applicable information available.

## 11. Toxicological information

### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

### Acute Toxicity/Effects

#### Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Of very high toxicity after short-term inhalation.

*Information on: (OLIGOMER) Hexamethylene diisocyanate isocyanurate-type oligomers*  
*Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic after a single skin contact. Of moderate toxicity after short-term inhalation.*

-----

# Safety Data Sheet

## DH105 HI TEMP LV HRDNR

Revision date : 2020/07/24  
Version: 5.0

Page: 7/9  
(30112193/SDS\_GEN\_CA/EN)

### Oral

Type of value: LD50  
Species: rat  
Value: > 5,000.000000 mg/kg

### Inhalation

Type of value: LC50  
Species: rat  
Value: 0.390000 mg/l

### Dermal

Type of value: LD50  
No applicable information available.

### Assessment other acute effects

Assessment of STOT single:  
Causes temporary irritation of the respiratory tract.

### Irritation / corrosion

Assessment of irritating effects: Skin contact causes irritation.

*Information on: (OLIGOMER) Hexamethylene diisocyanate isocyanurate-type oligomers*

*Assessment of irritating effects: May cause slight irritation to the skin. May cause slight irritation to the eyes.*

*Information on: 4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene*

*Assessment of irritating effects: May cause slight irritation to the skin. Not irritating to the eyes.*

### Sensitization

*Information on: (OLIGOMER) Hexamethylene diisocyanate isocyanurate-type oligomers*

*Assessment of sensitization:  
Caused skin sensitization in animal studies.*

### Aspiration Hazard

No applicable information available.

## Chronic Toxicity/Effects

### Repeated dose toxicity

Assessment of repeated dose toxicity: The product has not been tested. The statement has been derived from the properties of the individual components.

*Information on: (OLIGOMER) Hexamethylene diisocyanate isocyanurate-type oligomers*

*Assessment of repeated dose toxicity: After repeated exposure the prominent effect is local irritation.*

*Information on: 4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene*

*Assessment of repeated dose toxicity: Repeated exposure to the substance by oral administration leads to effects similar to those found after single exposure. Repeated exposure to the substance by inhalative administration leads to effects similar to those found after single exposure. May affect the liver and kidneys as indicated in animal studies. Overexposure may cause blood abnormalities.*

# Safety Data Sheet

## DH105 HI TEMP LV HRDNR

Revision date : 2020/07/24  
Version: 5.0

Page: 8/9  
(30112193/SDS\_GEN\_CA/EN)

### Carcinogenicity

Assessment of carcinogenicity: No data available concerning carcinogenic effects.

### Medical conditions aggravated by overexposure

Medical supervision of all employees who handle or come into contact with isocyanates is recommended. Persons with asthmatic conditions, chronic bronchitis, other chronic respiratory diseases, recurrent eczema or pulmonary sensitization should be excluded from working with isocyanates. Once a person is diagnosed as having pulmonary sensitization (allergic asthma) to isocyanates, further exposure is not recommended. The isocyanate component is a respiratory sensitizer. It may cause allergic reaction leading to asthma-like spasms of the bronchial tubes and difficulty in breathing.

---

## 12. Ecological Information

No applicable information available.

---

## 13. Disposal considerations

### **Waste disposal of substance:**

Do not discharge into drains/surface waters/groundwater.

Must be disposed of or incinerated in accordance with local regulations.

---

## 14. Transport Information

### **Land transport**

TDG

Hazard class:	3
Packing group:	III
ID number:	UN 1263
Hazard label:	3
Proper shipping name:	PAINT RELATED MATERIAL

### **Sea transport**

IMDG

Hazard class:	3
Packing group:	III
ID number:	UN 1263
Hazard label:	3
Marine pollutant:	NO
Proper shipping name:	PAINT RELATED MATERIAL

### **Air transport**

IATA/ICAO

Hazard class:	3
Packing group:	III
ID number:	UN 1263
Hazard label:	3
Proper shipping name:	PAINT RELATED MATERIAL



# Safety Data Sheet

## DH105 HI TEMP LV HRDNR

Revision date : 2020/07/24  
Version: 5.0

Page: 9/9  
(30112193/SDS\_GEN\_CA/EN)

---

### 15. Regulatory Information

#### Federal Regulations

##### **Registration status:**

Chemical DSL, CA released / listed

##### **NFPA Hazard codes:**

Health: 2 Fire: 2 Reactivity: 0 Special:

---

### 16. Other Information

#### **SDS Prepared by:**

BASF NA Product Regulations

SDS Prepared on: 2020/07/24

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

---

END OF DATA SHEET