



We create chemistry

Safety Data Sheet

SB04 Quick-Dry Color Boost

Revision date : 2020/07/24
Version: 6.0

Page: 1/9
(30592119/SDS_GEN_CA/EN)

1. Identification

Product identifier used on the label

SB04 Quick-Dry Color Boost

Recommended use of the chemical and restriction on use

Recommended use*: Paints, Coatings and Related Materials; for industrial use only

Unsuitable for use: Not intended for sale to or use by the general public.

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF Canada Inc.
100 Milverton Drive
Mississauga, ON L5R 4H1, CANADA

Telephone: +1 289 360-1300

Emergency telephone number

CHEMTREC: 1-800-424-9300
BASF HOTLINE: (800) 454-COPE (2673)

Other means of identification

Chemical family: Coating

2. Hazards Identification

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

Classification of the product

Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
STOT SE	3 (irritating to respiratory system)	Specific target organ toxicity — single exposure
Flam. Liq.	3	Flammable liquids

Label elements

Safety Data Sheet

SB04 Quick-Dry Color Boost

Revision date : 2020/07/24

Version: 6.0

Page: 2/9

(30592119/SDS_GEN_CA/EN)

Pictogram:



Signal Word:

Warning

Hazard Statement:

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P271	Use only outdoors or in a well-ventilated area.
P264	Wash contaminated body parts thoroughly after handling.
P242	Use only non-sparking tools.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P243	Take action to prevent static discharges.
P233	Keep container tightly closed.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground and bond container and receiving equipment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.

Precautionary Statements (Response):

P312	Call a POISON CENTER or physician if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P370 + P378	In case of fire: Use water spray for extinction.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P332 + P313	If skin irritation occurs: Get medical attention.
P303 + P361 + P353	IF ON SKIN (or hair): Remove or Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P337 + P313	If eye irritation persists: Get medical attention.

Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

Hazards not otherwise classified

No applicable information available.

Safety Data Sheet

SB04 Quick-Dry Color Boost

Revision date : 2020/07/24
Version: 6.0

Page: 3/9
(30592119/SDS_GEN_CA/EN)

3. Composition / Information on Ingredients

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

2-heptanone

CAS Number: 110-43-0
Content (W/W): ≥ 1.0 - $< 3.0\%$
Synonym: 2-Heptanone; Methyl n-amyl ketone

4-chloro- α,α,α -trifluorotoluene

CAS Number: 98-56-6
Content (W/W): ≥ 75.0 - $\leq 100.0\%$
Synonym: No data available.

4. First-Aid Measures

Description of first aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

If in eyes:

Flush with copious amounts of water for at least 15 minutes. Hold eyelids open to facilitate rinsing. If irritation develops, seek medical attention. Seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Information on: 2-heptanone

Symptoms: Overexposure may cause:, headache, dizziness, nausea, unconsciousness

Information on: 4-chloro- α,α,α -trifluorotoluene

Symptoms: Overexposure may cause:, lethargy, nausea, headache, dizziness

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Safety Data Sheet

SB04 Quick-Dry Color Boost

Revision date : 2020/07/24
Version: 6.0

Page: 4/9
(30592119/SDS_GEN_CA/EN)

Suitable extinguishing media:
carbon dioxide, foam, dry powder

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture

Advice for fire-fighters

Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Remove product from areas of fire, or otherwise cool sealed containers with water in order to avoid pressure build up due to heat.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Use antistatic tools. Wear suitable personal protective clothing and equipment. Ensure adequate ventilation.

Environmental precautions

Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

Dike spillage. Place into appropriately labeled waste containers.

7. Handling and Storage

Precautions for safe handling

Handle and open container with care. Use static lines when mixing and transferring material. Do not puncture, drop, or slide containers. Ensure adequate ventilation. Avoid contact with the skin, eyes and clothing.

Protection against fire and explosion:

Use antistatic tools. Exhaust fans should be explosion proof. Avoid all sources of ignition: heat, sparks, open flame. Sealed containers should be protected against heat as this results in pressure build-up.

Conditions for safe storage, including any incompatibilities

Segregate from oxidizing agents. Segregate from incompatible substances.

Further information on storage conditions: Protect from direct sunlight.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

2-heptanone	OSHA PEL	PEL 100 ppm 465 mg/m ³ ; TWA value 100 ppm 465 mg/m ³ ;
	ACGIH TLV	TWA value 50 ppm ;

Safety Data Sheet

SB04 Quick-Dry Color Boost

Revision date : 2020/07/24
Version: 6.0

Page: 5/9
(30592119/SDS_GEN_CA/EN)

Advice on system design:

Provide local exhaust ventilation to maintain recommended P.E.L.

Personal protective equipment

Respiratory protection:

Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination.

Hand protection:

Use appropriate chemically impervious gloves as determined by an evaluation of glove performance characteristics and the hazards and potential hazards identified, including but not limited to butyl, natural and synthetic rubber, nitrile, or neoprene.

Eye protection:

Wear face shield if splashing hazard exists. Tightly fitting safety goggles (chemical goggles).

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Work place should be equipped with a shower and an eye wash. Remove contaminated clothing. Remove contaminated clothing immediately and clean before re-use or dispose it if necessary. Contact lenses should not be worn. Hands and/or face should be washed before breaks and at the end of the shift.

9. Physical and Chemical Properties

Form:	liquid	
Odour:	of the solvent contained in the product	
Odour threshold:	No applicable information available.	
Colour:	colourless to yellow	
pH value:	No applicable information available.	
Melting point:	No applicable information available.	
Freezing point:	No applicable information available.	
Boiling range:	138.60 - 151.00 °C	
Sublimation point:	No applicable information available.	
Flash point:	36 °C	
Flammability:	No applicable information available.	
Lower explosion limit:	0.90 %(V)	
Upper explosion limit:	10.50 %(V)	
Autoignition:	No applicable information available.	
Vapour pressure:	No applicable information available.	
Density:	1.3225 g/cm3 (20 °C)	(calculated)
Relative density:	1.3225 (20 °C)	
Vapour density:	No applicable information available.	
Partitioning coefficient n-octanol/water (log Pow):	No applicable information available.	
Thermal decomposition:	No applicable information available.	
Viscosity, dynamic:	No applicable information available.	
Viscosity, kinematic:	No applicable information available.	
Solubility in water:	No applicable information available.	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Molar mass:	No applicable information available.	

Safety Data Sheet

SB04 Quick-Dry Color Boost

Revision date : 2020/07/24

Version: 6.0

Page: 6/9

(30592119/SDS_GEN_CA/EN)

Evaporation rate: No applicable information available.

10. Stability and Reactivity

Reactivity

No applicable information available.

Chemical stability

Possibility of hazardous reactions

No applicable information available.

Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge.

Incompatible materials

strong oxidizing agents

Hazardous decomposition products

Thermal decomposition:

No applicable information available.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact. Of moderate toxicity after single ingestion.

Information on: 2-heptanone

Assessment of acute toxicity: Of moderate toxicity after short-term inhalation. Of moderate toxicity after single ingestion. Virtually nontoxic after a single skin contact.

Oral

No applicable information available.

Type of value: LD50

Species: rat

Value: 1,670.000000 mg/kg

Inhalation

No applicable information available.

Type of value: LC50

Species: rat

Value: 19.000000 mg/l

Safety Data Sheet

SB04 Quick-Dry Color Boost

Revision date : 2020/07/24

Version: 6.0

Page: 7/9

(30592119/SDS_GEN_CA/EN)

Dermal

No applicable information available.

Type of value: LD50

Species: rabbit

Value: 10,000.000000 mg/kg

Assessment other acute effects

Assessment of STOT single:

Causes temporary irritation of the respiratory tract.

Irritation / corrosion

Information on: 2-heptanone

Assessment of irritating effects: Not irritating to the eyes. May cause slight irritation to the skin.

Information on: 4-chloro- α,α,α -trifluorotoluene

Assessment of irritating effects: May cause slight irritation to the skin. Not irritating to the eyes.

Aspiration Hazard

No applicable information available.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: 4-chloro- α,α,α -trifluorotoluene

Assessment of repeated dose toxicity: Repeated exposure to the substance by oral administration leads to effects similar to those found after single exposure. Repeated exposure to the substance by inhalative administration leads to effects similar to those found after single exposure. May affect the liver and kidneys as indicated in animal studies. Overexposure may cause blood abnormalities.

Carcinogenicity

Assessment of carcinogenicity: No data available concerning carcinogenic effects.

12. Ecological Information

Additional information

Other ecotoxicological advice:

Acutely toxic for aquatic organisms.

13. Disposal considerations

Waste disposal of substance:

Do not discharge into drains/surface waters/groundwater.

Must be disposed of or incinerated in accordance with local regulations.

Safety Data Sheet

SB04 Quick-Dry Color Boost

Revision date : 2020/07/24
Version: 6.0

Page: 8/9
(30592119/SDS_GEN_CA/EN)

14. Transport Information

Land transport

TDG

Hazard class: 3
Packing group: III
ID number: UN 1866
Hazard label: 3
Proper shipping name: RESIN SOLUTION

Sea transport

IMDG

Hazard class: 3
Packing group: III
ID number: UN 1866
Hazard label: 3
Marine pollutant: NO
Proper shipping name: RESIN SOLUTION

Air transport

IATA/ICAO

Hazard class: 3
Packing group: III
ID number: UN 1866
Hazard label: 3
Proper shipping name: RESIN SOLUTION

15. Regulatory Information

Federal Regulations

Registration status:

Chemical DSL, CA released / listed

NFPA Hazard codes:

Health: 2 Fire: 3 Reactivity: 0 Special:

16. Other Information

SDS Prepared by:

BASF NA Product Regulations
SDS Prepared on: 2020/07/24

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our

Safety Data Sheet

SB04 Quick-Dry Color Boost

Revision date : 2020/07/24

Page: 9/9

Version: 6.0

(30592119/SDS_GEN_CA/EN)

operations on society and the environment during production, storage, transport, use and disposal of our products.

END OF DATA SHEET