

# Safety Data Sheet

## SB202 Deep Black II

Revision date : 2019/08/28  
Version: 6.0

Page: 1/11  
(30617760/SDS\_GEN\_CA/EN)

### 1. Identification

#### Product identifier used on the label

## SB202 Deep Black II

#### Recommended use of the chemical and restriction on use

Recommended use\*: for industrial use only

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

#### Details of the supplier of the safety data sheet

##### Company:

BASF Canada Inc.  
100 Milverton Drive  
Mississauga, ON L5R 4H1, CANADA

Telephone: +1 289 360-1300

#### Emergency telephone number

CHEMTREC: 1-800-424-9300  
BASF HOTLINE: (800) 454-COPE (2673)

#### Other means of identification

Chemical family: Coating

### 2. Hazards Identification

#### According to Hazardous Products Regulations (HPR) (SOR/2015-17)

#### Classification of the product

Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	1	Serious eye damage/eye irritation
Skin Sens.	1	Skin sensitization
STOT SE	3 (Vapours may cause drowsiness and dizziness.)	Specific target organ toxicity — single exposure
Flam. Liq.	3	Flammable liquids

#### Label elements

# Safety Data Sheet

## SB202 Deep Black II

Revision date : 2019/08/28  
Version: 6.0

Page: 2/11  
(30617760/SDS\_GEN\_CA/EN)

Pictogram:



Signal Word:  
Danger

Hazard Statement:

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.

Precautionary Statements (Prevention):

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P271	Use only outdoors or in a well-ventilated area.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash with plenty of water and soap thoroughly after handling.
P242	Use only non-sparking tools.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P243	Take action to prevent static discharges.
P233	Keep container tightly closed.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground and bond container and receiving equipment.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P370 + P378	In case of fire: Use water spray for extinction.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P310	Immediately call a POISON CENTER or doctor/physician.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents/container to hazardous or special waste collection point.
------	---

### Hazards not otherwise classified

No applicable information available.

# Safety Data Sheet

## SB202 Deep Black II

Revision date : 2019/08/28  
Version: 6.0

Page: 3/11  
(30617760/SDS\_GEN\_CA/EN)

### 3. Composition / Information on Ingredients

#### According to Hazardous Products Regulations (HPR) (SOR/2015-17)

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
78-92-2	>= 1.0 - < 3.0%	butan-2-ol
107-98-2	>= 25.0 - < 50.0%	1-methoxypropan-2-ol
108-01-0	>= 1.0 - < 3.0%	2-dimethylaminoethanol
111-76-2	>= 3.0 - < 5.0%	2-butoxyethanol
126-86-3	>= 3.0 - < 5.0%	2,4,7,9-Tetramethyldec-5-yne-4,7-diol
1333-86-4	>= 3.0 - < 5.0%	carbon black
7727-43-7	>= 1.0 - < 3.0%	Barium sulfate
108-65-6	>= 15.0 - < 20.0%	1-methoxy-2-propylacetate

### 4. First-Aid Measures

#### Description of first aid measures

##### General advice:

Remove contaminated clothing.

##### If inhaled:

Keep patient calm, remove to fresh air. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

##### If on skin:

Seek medical attention. Immediately wash affected area with soap and water for 20-30 minutes or until chemical is removed.

##### If in eyes:

Flush with copious amounts of water for at least 15 minutes. Hold eyelids open to facilitate rinsing. If irritation develops, seek medical attention. Seek medical attention.

##### If swallowed:

Immediate medical attention required. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Do not induce vomiting. Rinse mouth and then drink 200-300 ml of water.

#### Most important symptoms and effects, both acute and delayed

Symptoms: Additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

#### Indication of any immediate medical attention and special treatment needed

##### Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

# Safety Data Sheet

## SB202 Deep Black II

Revision date : 2019/08/28  
Version: 6.0

Page: 4/11  
(30617760/SDS\_GEN\_CA/EN)

### 5. Fire-Fighting Measures

#### Extinguishing media

Suitable extinguishing media:  
carbon dioxide, foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:  
water jet

#### Special hazards arising from the substance or mixture

Hazards during fire-fighting:

Vapors and/or decomposition products are irritant and/or toxic. If product is heated above decomposition temperature acrid smoke and fumes will be released.

#### Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

#### Further information:

Notify proper authorities. Do not flood burning material with water due to potential spreading of fire. Flash fire may occur. Run-off water from fire may cause pollution. Contain contaminated water/firefighting water. Remove product from areas of fire, or otherwise cool sealed containers with water in order to avoid pressure build up due to heat. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Use antistatic tools. Extinguish sources of ignition nearby and downwind. Avoid prolonged inhalation. Wear suitable personal protective clothing and equipment. Ensure adequate ventilation.

#### Environmental precautions

Do not discharge into drains/surface waters/groundwater.

#### Methods and material for containment and cleaning up

Dike spillage. Spills should be contained, solidified, and placed in suitable containers for disposal. Place into appropriately labeled waste containers.

### 7. Handling and Storage

#### Precautions for safe handling

Handle and open container with care. WARNING: Empty containers may still contain hazardous residue. Use static lines when mixing and transferring material. Do not puncture, drop, or slide containers. Ensure adequate ventilation. Avoid contact with the skin, eyes and clothing.

Protection against fire and explosion:

Risk of explosion if heated under confinement. Use antistatic tools. Exhaust fans should be explosion proof. Avoid all sources of ignition: heat, sparks, open flame. Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources. Sealed containers should be protected against heat as this results in pressure build-up.

#### Conditions for safe storage, including any incompatibilities

# Safety Data Sheet

## SB202 Deep Black II

Revision date : 2019/08/28  
Version: 6.0

Page: 5/11  
(30617760/SDS\_GEN\_CA/EN)

Segregate from strong bases. Segregate from oxidizing agents. Segregate from incompatible substances. Segregate from strong acids.

Suitable materials for containers: Carbon steel (Iron), tinned carbon steel (Tinplate), Stove-lacquer Valspar HXR008F red, Stove-lacquer KNS L-5X

Further information on storage conditions: Keep container tightly closed. Protect from direct sunlight.

Storage stability:  
Consult local fire marshal for storage requirements.  
Protect from temperatures above: 49 °C

## 8. Exposure Controls/Personal Protection

### Components with occupational exposure limits

butan-2-ol	OSHA PEL	PEL 150 ppm 450 mg/m3 ; TWA value 100 ppm 305 mg/m3 ;
	ACGIH TLV	TWA value 100 ppm ;
1-methoxypropan-2-ol	OSHA PEL	TWA value 100 ppm 360 mg/m3 ; STEL value 150 ppm 540 mg/m3 ;
	ACGIH TLV	TWA value 50 ppm ; STEL value 100 ppm ;
2-butoxyethanol	OSHA PEL	PEL 50 ppm 240 mg/m3 ; Skin Designation ; The substance can be absorbed through the skin. SKIN_FINAL ; The substance can be absorbed through the skin.
	ACGIH TLV	TWA value 25 ppm 120 mg/m3 ; TWA value 20 ppm ;
carbon black	OSHA PEL	PEL 3.5 mg/m3 ; TWA value 3.5 mg/m3 ;
	ACGIH TLV	TWA value 3 mg/m3 Inhalable fraction ;
Barium sulfate	OSHA PEL	PEL 15 mg/m3 Total dust ; PEL 5 mg/m3 Respirable fraction ;
	ACGIH TLV	TWA value 5 mg/m3 Inhalable fraction ; The value is for particulate matter containing no asbestos and <1% crystalline silica.

### **Advice on system design:**

Provide local exhaust ventilation to maintain recommended P.E.L.

### **Personal protective equipment**

#### **Respiratory protection:**

Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination. Wear a NIOSH-certified (or equivalent) organic vapour respirator. Particulate filters should be added during spray operations. Wear respiratory protection if ventilation is inadequate.

#### **Hand protection:**

Chemical resistant protective gloves

#### **Eye protection:**

Wear face shield if splashing hazard exists. Tightly fitting safety goggles (chemical goggles).

# Safety Data Sheet

## SB202 Deep Black II

Revision date : 2019/08/28  
Version: 6.0

Page: 6/11  
(30617760/SDS\_GEN\_CA/EN)

### Body protection:

Body protection must be chosen based on level of activity and exposure.

### General safety and hygiene measures:

Work place should be equipped with a shower and an eye wash. Remove contaminated clothing. Remove contaminated clothing immediately and clean before re-use or dispose it if necessary. Contact lenses should not be worn. Hands and/or face should be washed before breaks and at the end of the shift.

## 9. Physical and Chemical Properties

Form:	liquid	
Odour:	of the solvent contained in the product	
Odour threshold:	No applicable information available.	
Colour:	black	
pH value:	No applicable information available.	
Melting point:	No applicable information available.	
Boiling range:	100.00 - 171.00 °C	
Sublimation point:	No applicable information available.	
Flash point:	32.22 °C	(ASTM D3278)
Flammability:	No applicable information available.	
Lower explosion limit:	1.50 %(V)	
Upper explosion limit:	13.74 %(V)	
Autoignition:	No applicable information available.	
Vapour pressure:	No applicable information available.	
Density:	1.0035 g/cm <sup>3</sup> ( 20 °C)	(calculated)
Relative density:	1.0035 ( 20 °C)	
Vapour density:	No applicable information available.	
Partitioning coefficient n-octanol/water (log Pow):	No applicable information available.	
Thermal decomposition:	No applicable information available.	
Viscosity, dynamic:	No applicable information available.	
Viscosity, kinematic:	> 20.600 mm <sup>2</sup> /s	
Solubility in water:	No applicable information available.	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Molar mass:	No applicable information available.	
Evaporation rate:	No applicable information available.	

## 10. Stability and Reactivity

### Reactivity

No applicable information available.

### Chemical stability

The product is chemically stable.

### Possibility of hazardous reactions

No applicable information available.

### Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge.

### Incompatible materials

# Safety Data Sheet

## SB202 Deep Black II

Revision date : 2019/08/28  
Version: 6.0

Page: 7/11  
(30617760/SDS\_GEN\_CA/EN)

strong oxidizing agents, strong bases, strong acids

### Hazardous decomposition products

Decomposition products:  
carbon dioxide, carbon monoxide

Thermal decomposition:  
No applicable information available.

## 11. Toxicological information

### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

#### Primary routes of entry

Solvents are absorbed through the skin.

### Acute Toxicity/Effects

#### Acute toxicity

Assessment of acute toxicity: Virtually nontoxic by inhalation. Of moderate toxicity after short-term skin contact. Of moderate toxicity after single ingestion.

#### *Information on: 1-methoxypropan-2-ol*

*Assessment of acute toxicity: Of low toxicity after single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact.*

#### *Information on: 2-dimethylaminoethanol*

*Assessment of acute toxicity: Of moderate toxicity after short-term skin contact. Of moderate toxicity after single ingestion. Of pronounced toxicity after short-term inhalation.*

#### *Information on: 2-butoxyethanol*

*Assessment of acute toxicity: Of moderate toxicity after single ingestion. The inhalation of a highly enriched/saturated vapor-air-mixture represents an unlikely acute hazard. The European Union (EU) has classified this substance as 'harmful' after inhalation. Virtually nontoxic after a single skin contact. The European Union (EU) has classified this substance as 'harmful' after dermal exposure.*

#### Oral

Type of value: LD50

Species: rat

Value:  $\geq 1,183.00000$  mg/kg

#### Inhalation

Type of value: LC50

Species: rat

Value:  $> 6.000000$  mg/l

#### Dermal

Type of value: LD50

Species: rabbit

Value:  $\geq 1,219.00000$  mg/kg

# Safety Data Sheet

## SB202 Deep Black II

Revision date : 2019/08/28  
Version: 6.0

Page: 8/11  
(30617760/SDS\_GEN\_CA/EN)

### Assessment other acute effects

Assessment of STOT single:

Possible narcotic effects (drowsiness or dizziness).

### Irritation / corrosion

Assessment of irritating effects: Corrosive. Eye contact causes irritation.

*Information on: 1-methoxypropan-2-ol*

*Assessment of irritating effects: Not irritating to the skin. Not irritating to the eyes.*

*Information on: 2-dimethylaminoethanol*

*Assessment of irritating effects: Corrosive! Damages skin and eyes.*

*Information on: 2-butoxyethanol*

*Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.*

*Information on: 2,4,7,9-Tetramethyldec-5-yne-4,7-diol*

*Assessment of irritating effects: Not irritating to the skin. May cause severe damage to the eyes.*

*Information on: 1-methoxy-2-propylacetate*

*Assessment of irritating effects: Not irritating to the skin. Not irritating to the eyes.*

### Sensitization

*Information on: 2,4,7,9-Tetramethyldec-5-yne-4,7-diol*

*Assessment of sensitization:*

*Caused skin sensitization in animal studies.*

### Aspiration Hazard

No applicable information available.

## Chronic Toxicity/Effects

### Repeated dose toxicity

Assessment of repeated dose toxicity: The product has not been tested. The statement has been derived from the properties of the individual components.

*Information on: 1-methoxypropan-2-ol*

*Assessment of repeated dose toxicity: May affect the liver as indicated in animal studies. The substance may cause damage to the kidney after repeated inhalation. Effect found in rodents only. The relevance to humans is questionable.*

*Information on: 2-dimethylaminoethanol*

*Assessment of repeated dose toxicity: The substance may cause damage to the central nervous system after repeated ingestion of high doses. The results are preliminary and do not provide a complete understanding of the effect observed.*

*Information on: carbon black*

*Assessment of repeated dose toxicity: Chronic exposures have been known to produce pneumoconiosis (chronic inflammatory and fibrotic lung disease). The substance may cause increase in lung mass and lung tissue changes after repeated inhalation. Repeated oral uptake of the substance did not cause substance-related effects. Repeated dermal uptake of the substance did not cause substance-related effects.*

*Information on: 1-methoxy-2-propylacetate*



# Safety Data Sheet

## SB202 Deep Black II

Revision date : 2019/08/28  
Version: 6.0

Page: 9/11  
(30617760/SDS\_GEN\_CA/EN)

*Assessment of repeated dose toxicity: Repeated dermal uptake of the substance did not cause substance-related effects. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The substance may cause damage to the olfactory epithelium after repeated inhalation. Repeated oral uptake of the substance did not cause substance-related effects.*

-----

### Genetic toxicity

*Information on: carbon black*

*Assessment of mutagenicity: Results from a number of mutagenicity studies with microorganisms and mammalian cell culture are available. Taking into account all of the information, there is no indication that the substance is mutagenic. Based on the structure, there is a suspicion of a mutagenic effect.*

*The substance was genotoxic in a test with mammals. The effect may result from a secondary mechanism.*

-----

*Information on: carbon black*

*Assessment of mutagenicity: Results from a number of mutagenicity studies with microorganisms and mammalian cell culture are available. Taking into account all of the information, there is no indication that the substance is mutagenic. Based on the structure, there is a suspicion of a mutagenic effect.*

*The substance was genotoxic in a test with mammals. The effect may result from a secondary mechanism.*

-----

### Carcinogenicity

*Assessment of carcinogenicity: Contains a suspect carcinogen.*

*Information on: 2-dimethylaminoethanol*

*Assessment of carcinogenicity: Under certain conditions the substance can form nitrosamines.*

*Nitrosamines are carcinogenic in animal studies. In long-term animal studies in which the substance was given by inhalation in high concentrations, a carcinogenic effect was not observed.*

*Information on: 2-butoxyethanol*

*Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. A clear indication of an increased risk of cancer in humans has so far not been shown. IARC Group 3 (not classifiable as to human carcinogenicity).*

*Information on: carbon black*

*Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term animal studies in which the substance was given by inhalation in high concentrations, a carcinogenic effect was observed. A clear indication of an increased risk of cancer in humans has so far not been shown. No carcinogenic potential can be deduced from other studies with rats and mice.*

*The American Conference of Governmental Industrial Hygienists (ACGIH) has classified this substance as Group A3 - animal carcinogen.*

-----

### Reproductive toxicity

*Information on: 1-methoxypropan-2-ol*

# Safety Data Sheet

## SB202 Deep Black II

Revision date : 2019/08/28  
Version: 6.0

Page: 10/11  
(30617760/SDS\_GEN\_CA/EN)

*Assessment of reproduction toxicity: The potential to impair fertility cannot be excluded when given at maternally toxic doses.*

*Information on: 2-dimethylaminoethanol*

*Assessment of reproduction toxicity: The results of animal studies suggest a fertility impairing effect. The results were determined in a Screening test. On the basis of currently available information, a final assessment is not possible.*

### Teratogenicity

*Information on: 1-methoxypropan-2-ol*

*Assessment of teratogenicity: No indications of a developmental toxic / teratogenic effect were seen in animal studies.*

*Information on: 2-dimethylaminoethanol*

*Assessment of teratogenicity: Causes developmental effects in animals at high, maternally toxic doses.*

*Information on: 2-dimethylaminoethanol*

*Assessment of teratogenicity: Causes developmental effects in animals at high, maternally toxic doses.*

### **Symptoms of Exposure**

Additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

## **12. Ecological Information**

No applicable information available.

## **13. Disposal considerations**

### **Waste disposal of substance:**

Do not incinerate closed containers. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. Do not discharge into drains/surface waters/groundwater.

Must be disposed of or incinerated in accordance with local regulations.

### **Container disposal:**

WARNING: Empty containers may still contain hazardous residue.

## **14. Transport Information**

### **Land transport**

TDG

Hazard class:	3
Packing group:	III
ID number:	UN 1263
Hazard label:	3

# Safety Data Sheet

## SB202 Deep Black II

Revision date : 2019/08/28  
Version: 6.0

Page: 11/11  
(30617760/SDS\_GEN\_CA/EN)

Proper shipping name: PAINT

### Sea transport

IMDG

Hazard class: 3  
Packing group: III  
ID number: UN 1263  
Hazard label: 3  
Marine pollutant: NO  
Proper shipping name: PAINT

### Air transport

IATA/ICAO

Hazard class: 3  
Packing group: III  
ID number: UN 1263  
Hazard label: 3  
Proper shipping name: PAINT

## 15. Regulatory Information

### Federal Regulations

#### Registration status:

Chemical DSL, CA released; restriction on quantity / not listed

#### NFPA Hazard codes:

Health: 3 Fire: 3 Reactivity: 0 Special:

## 16. Other Information

### SDS Prepared by:

BASF NA Product Regulations  
SDS Prepared on: 2019/08/28

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

END OF DATA SHEET