



We create chemistry

# Safety Data Sheet

## SC90 UNO HD WHITE.

Revision date : 2021/06/07  
Version: 6.0

Page: 1/12  
(30669052/SDS\_GEN\_CA/EN)

### 1. Identification

#### Product identifier used on the label

**SC90 UNO HD WHITE.**

#### Recommended use of the chemical and restriction on use

Recommended use\*: Monocoat product

Recommended use\*: Paints, Coatings and Related Materials; for industrial use only

Unsuitable for use: Not intended for sale to or use by the general public.

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

#### Details of the supplier of the safety data sheet

##### Company:

BASF Canada Inc.  
100 Milverton Drive  
Mississauga, ON L5R 4H1, CANADA

Telephone: +1 289 360-1300

#### Emergency telephone number

##### 24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300

BASF HOTLINE: (800) 454-COPE (2673)

#### Other means of identification

Chemical family: Coating

### 2. Hazards Identification

#### According to Hazardous Products Regulations (HPR) (SOR/2015-17)

#### Classification of the product

|                   |   |                                                |
|-------------------|---|------------------------------------------------|
| Skin Corr./Irrit. | 2 | Skin corrosion/irritation                      |
| Flam. Liq.        | 3 | Flammable liquids                              |
| Aquatic Acute     | 3 | Hazardous to the aquatic environment - acute   |
| Aquatic Chronic   | 3 | Hazardous to the aquatic environment - chronic |
| STOT RE           | 2 | Specific target organ toxicity — repeated      |

# Safety Data Sheet

## SC90 UNO HD WHITE.

Revision date : 2021/06/07  
Version: 6.0

Page: 2/12  
(30669052/SDS\_GEN\_CA/EN)

exposure

### Label elements

Pictogram:



Signal Word:  
Warning

Hazard Statement:

|      |                                                                                                            |
|------|------------------------------------------------------------------------------------------------------------|
| H226 | Flammable liquid and vapour.                                                                               |
| H315 | Causes skin irritation.                                                                                    |
| H373 | May cause damage to organs (Central nervous system, Kidney, Liver) through prolonged or repeated exposure. |
| H412 | Harmful to aquatic life with long lasting effects.                                                         |

Precautionary Statements (Prevention):

|      |                                                                                                |
|------|------------------------------------------------------------------------------------------------|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P260 | Do not breathe dust or mist.                                                                   |
| P273 | Avoid release to the environment.                                                              |
| P280 | Wear protective gloves, protective clothing and eye protection or face protection.             |
| P240 | Ground and bond container and receiving equipment.                                             |
| P233 | Keep container tightly closed.                                                                 |
| P243 | Take action to prevent static discharges.                                                      |
| P241 | Use explosion-proof electrical, ventilating and lighting equipment.                            |
| P242 | Use only non-sparking tools.                                                                   |
| P264 | Wash contaminated body parts thoroughly after handling.                                        |

Precautionary Statements (Response):

|                    |                                                                                                                  |
|--------------------|------------------------------------------------------------------------------------------------------------------|
| P314               | Get medical advice/attention if you feel unwell.                                                                 |
| P303 + P361 + P353 | IF ON SKIN (or hair): Remove or Take off immediately all contaminated clothing. Rinse skin with water or shower. |
| P332 + P313        | If skin irritation occurs: Get medical attention.                                                                |
| P362 + P364        | Take off contaminated clothing and wash it before reuse.                                                         |
| P370 + P378        | In case of fire: Use water spray for extinction.                                                                 |
| P302 + P352        | IF ON SKIN: Wash with plenty of soap and water.                                                                  |

Precautionary Statements (Storage):

|             |                                              |
|-------------|----------------------------------------------|
| P403 + P235 | Store in a well-ventilated place. Keep cool. |
|-------------|----------------------------------------------|

Precautionary Statements (Disposal):

|      |                                                                                   |
|------|-----------------------------------------------------------------------------------|
| P501 | Dispose of contents and container to hazardous or special waste collection point. |
|------|-----------------------------------------------------------------------------------|

### Hazards not otherwise classified

No applicable information available.

## 3. Composition / Information on Ingredients

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

# Safety Data Sheet

## SC90 UNO HD WHITE.

Revision date : 2021/06/07  
Version: 6.0

Page: 3/12  
(30669052/SDS\_GEN\_CA/EN)

1,2,4-trimethylbenzene

CAS Number: 95-63-6

Content (W/W):  $\geq 5.0$  -  $< 7.0\%$

Synonym: 1,2,4-Trimethylbenzene

ethylbenzene

CAS Number: 100-41-4

Content (W/W):  $\geq 0.3$  -  $< 1.0\%$

Synonym: Ethylbenzene

mesitylene

CAS Number: 108-67-8

Content (W/W):  $\geq 1.0$  -  $< 3.0\%$

Synonym: 1,3,5-Trimethylbenzene

n-Butyl acetate

CAS Number: 123-86-4

Content (W/W):  $\geq 7.0$  -  $< 10.0\%$

Synonym: n-Butyl acetate

Xylene

CAS Number: 1330-20-7

Content (W/W):  $\geq 1.0$  -  $< 3.0\%$

Synonym: Xylene; Dimethylbenzene

Solvent naphtha (petroleum), light arom.

CAS Number: 64742-95-6

Content (W/W):  $\geq 7.0$  -  $< 10.0\%$

Synonym: No data available.

quartz, crystalline

CAS Number: 14808-60-7

Content (W/W):  $\geq 0.0$  -  $< 0.1\%$

Synonym: No data available.

Titanium oxide (TiO<sub>2</sub>)

CAS Number: 13463-67-7

Content (W/W):  $\geq 25.0$  -  $< 50.0\%$

Synonym: Titanium dioxide

---

## 4. First-Aid Measures

### Description of first aid measures

#### General advice:

Remove contaminated clothing.

#### If inhaled:

Keep patient calm, remove to fresh air. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

#### If on skin:

If irritation develops, seek medical attention. Wash affected areas with water for at least 15 minutes.

# Safety Data Sheet

## SC90 UNO HD WHITE.

Revision date : 2021/06/07  
Version: 6.0

Page: 4/12  
(30669052/SDS\_GEN\_CA/EN)

### **If in eyes:**

Flush with copious amounts of water for at least 15 minutes. Hold eyelids open to facilitate rinsing. If irritation develops, seek medical attention. Seek medical attention.

### **If swallowed:**

Immediate medical attention required. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Do not induce vomiting. Rinse mouth and then drink 200-300 ml of water.

## **Most important symptoms and effects, both acute and delayed**

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

*Information on: 1,2,4-trimethylbenzene*

*Symptoms: Overexposure may cause:, headache, tiredness, nausea, anxiety, asthma, bronchitis, noncardiogenic pulmonary edema*

*Information on: mesitylene*

*Symptoms: Overexposure may cause:, Eye irritation, skin irritation, irritation of the mucous membranes, bronchitis, anemia, erythema, nausea, headache, weakness, tiredness, confusion, vomiting, dizziness, diarrhea, abdominal cramps, Inhalation may provoke the following symptoms:, irritation of respiratory tract, coughing, Ingestion may provoke the following symptoms:, asphyxia, dyspnea, choking, pneumonitis, respiratory arrest, circulatory collapse, death*

*Information on: Xylene*

*Symptoms: Overexposure may cause:, coma, weakness, lethargy, confusion, dyspnea, nausea, headache, dizziness*

*Information on: Solvent naphtha (petroleum), light arom.*

*Symptoms: Overexposure may cause:, Eye irritation, skin irritation, erythema, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps, Ingestion may provoke the following symptoms:, asphyxia, dyspnea, choking, respiratory arrest, circulatory collapse, death*

*Information on: quartz, crystalline*

*Symptoms: Overexposure may cause:, rhinitis, irritation of the mucous membranes, irritates the eyes and respiratory tract, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps*

-----

## **Indication of any immediate medical attention and special treatment needed**

### Note to physician

|            |                                                                                             |
|------------|---------------------------------------------------------------------------------------------|
| Treatment: | Treat according to symptoms (decontamination, vital functions), no known specific antidote. |
|------------|---------------------------------------------------------------------------------------------|

---

## **5. Fire-Fighting Measures**

### **Extinguishing media**

Suitable extinguishing media:  
carbon dioxide, foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:  
water jet

# Safety Data Sheet

## SC90 UNO HD WHITE.

Revision date : 2021/06/07  
Version: 6.0

Page: 5/12  
(30669052/SDS\_GEN\_CA/EN)

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:

Vapors and/or decomposition products are irritant and/or toxic. If product is heated above decomposition temperature acrid smoke and fumes will be released.

### Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

### Further information:

Notify proper authorities. Do not flood burning material with water due to potential spreading of fire. Flash fire may occur. Run-off water from fire may cause pollution. Contain contaminated water/firefighting water. Remove product from areas of fire, or otherwise cool sealed containers with water in order to avoid pressure build up due to heat. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

---

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Use antistatic tools. Extinguish sources of ignition nearby and downwind. Avoid prolonged inhalation. Wear suitable personal protective clothing and equipment. Ensure adequate ventilation.

### Environmental precautions

Do not discharge into drains/surface waters/groundwater.

### Methods and material for containment and cleaning up

Dike spillage. Spills should be contained, solidified, and placed in suitable containers for disposal. Place into appropriately labeled waste containers.

---

## 7. Handling and Storage

### Precautions for safe handling

Handle and open container with care. WARNING: Empty containers may still contain hazardous residue. Use static lines when mixing and transferring material. Do not puncture, drop, or slide containers. Ensure adequate ventilation. Avoid contact with the skin, eyes and clothing.

Protection against fire and explosion:

Risk of explosion if heated under confinement. Use antistatic tools. Exhaust fans should be explosion proof. Avoid all sources of ignition: heat, sparks, open flame. Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources. Sealed containers should be protected against heat as this results in pressure build-up.

### Conditions for safe storage, including any incompatibilities

Segregate from strong bases. Segregate from oxidizing agents. Segregate from incompatible substances. Segregate from strong acids.

Suitable materials for containers: Stove-lacquer R 78433, Stove-lacquer EHD0022, High density polyethylene (HDPE), Low density polyethylene (LDPE), Polyethylenetherephthalate (PET), Polypropylene (PP), Stainless steel 1.4301 (V2), Carbon steel (Iron), tinned carbon steel (Tinplate)

Further information on storage conditions: Keep container tightly closed. Protect from direct sunlight.

# Safety Data Sheet

## SC90 UNO HD WHITE.

Revision date : 2021/06/07

Version: 6.0

Page: 6/12

(30669052/SDS\_GEN\_CA/EN)

Storage stability:  
Consult local fire marshal for storage requirements.  
Protect from temperatures above: 49 °C

### 8. Exposure Controls/Personal Protection

#### Components with occupational exposure limits

|                        |            |                                                  |
|------------------------|------------|--------------------------------------------------|
| 1,2,4-trimethylbenzene | ACGIH, US: | TWA value 25 ppm ;                               |
|                        | OSHA Z1A:  | TWA value 25 ppm 125 mg/m3 ;                     |
| ethylbenzene           | ACGIH, US: | TWA value 20 ppm ;                               |
|                        | OSHA Z1:   | PEL 100 ppm 435 mg/m3 ;                          |
|                        | OSHA Z1A:  | STEL value 125 ppm 545 mg/m3 ;                   |
|                        | OSHA Z1A:  | TWA value 100 ppm 435 mg/m3 ;                    |
| mesitylene             | ACGIH, US: | TWA value 25 ppm ;                               |
|                        | OSHA Z1A:  | TWA value 25 ppm 125 mg/m3 ;                     |
| n-Butyl acetate        | ACGIH, US: | STEL value 150 ppm ;                             |
|                        | ACGIH, US: | TWA value 50 ppm ;                               |
|                        | OSHA Z1:   | PEL 150 ppm 710 mg/m3 ;                          |
|                        | OSHA Z1A:  | STEL value 200 ppm 950 mg/m3 ;                   |
|                        | OSHA Z1A:  | TWA value 150 ppm 710 mg/m3 ;                    |
| Xylene                 | ACGIH, US: | TWA value 100 ppm ;                              |
|                        | ACGIH, US: | STEL value 150 ppm ;                             |
|                        | OSHA Z1:   | PEL 100 ppm 435 mg/m3 ;                          |
|                        | OSHA Z1A:  | TWA value 100 ppm 435 mg/m3 ;                    |
|                        | OSHA Z1A:  | STEL value 150 ppm 655 mg/m3 ;                   |
| quartz, crystalline    | OSHA, US:  | TWA value 0.05 mg/m3 (Respirable dust);          |
|                        | OSHA, US:  | OSHA Action level 0.025 mg/m3 (Respirable dust); |
|                        | ACGIH, US: | TWA value 0.025 mg/m3 Respirable fraction ;      |
| Titanium oxide (TiO2)  | ACGIH, US: | TWA value 10 mg/m3 ;                             |
|                        | OSHA Z1:   | PEL 15 mg/m3 Total dust ;                        |
|                        | OSHA Z1A:  | TWA value 10 mg/m3 Total dust ;                  |
|                        | OSHA Z3:   | TWA value 15 mg/m3 Total dust ;                  |
|                        | OSHA Z3:   | TWA value 5 mg/m3 Respirable fraction ;          |

#### **Advice on system design:**

Provide local exhaust ventilation to maintain recommended P.E.L.

# Safety Data Sheet

## SC90 UNO HD WHITE.

Revision date : 2021/06/07  
Version: 6.0

Page: 7/12  
(30669052/SDS\_GEN\_CA/EN)

### Personal protective equipment

#### **Respiratory protection:**

Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination. Respiratory protection may not be required under normal operating conditions if adequate ventilation is provided. Wear a NIOSH-certified (or equivalent) organic vapour respirator. Particulate filters should be added during spray operations. Wear respiratory protection if ventilation is inadequate.

#### **Hand protection:**

Use appropriate chemically impervious gloves as determined by an evaluation of glove performance characteristics and the hazards and potential hazards identified, including but not limited to butyl, natural and synthetic rubber, nitrile, or neoprene.

#### **Eye protection:**

Wear face shield if splashing hazard exists. Tightly fitting safety goggles (chemical goggles).

#### **Body protection:**

Body protection must be chosen based on level of activity and exposure.

#### **General safety and hygiene measures:**

Work place should be equipped with a shower and an eye wash. Remove contaminated clothing. Remove contaminated clothing immediately and clean before re-use or dispose it if necessary. Contact lenses should not be worn. Hands and/or face should be washed before breaks and at the end of the shift.

## 9. Physical and Chemical Properties

|                                                     |                                      |              |
|-----------------------------------------------------|--------------------------------------|--------------|
| Form:                                               | liquid                               |              |
| Odour:                                              | No data available.                   |              |
| Odour threshold:                                    | No applicable information available. |              |
| Colour:                                             | white                                |              |
| pH value:                                           | No applicable information available. |              |
| Melting point:                                      | No applicable information available. |              |
| Freezing point:                                     | No applicable information available. |              |
| Boiling range:                                      | No applicable information available. |              |
| Sublimation point:                                  | No applicable information available. |              |
| Flash point:                                        | 34 °C                                | (ISO 3679)   |
| Flammability:                                       | No applicable information available. |              |
| Lower explosion limit:                              | No applicable information available. |              |
| Upper explosion limit:                              | No applicable information available. |              |
| Autoignition:                                       | No applicable information available. |              |
| Vapour pressure:                                    | No applicable information available. |              |
| Density:                                            | 1.3919 g/cm <sup>3</sup><br>( 20 °C) | (calculated) |
| Relative density:                                   | 1.3920<br>( 20 °C)                   |              |
| Vapour density:                                     | No applicable information available. |              |
| Partitioning coefficient n-octanol/water (log Pow): | No applicable information available. |              |
| Thermal decomposition:                              | No applicable information available. |              |
| Viscosity, dynamic:                                 | No applicable information available. |              |
| Viscosity, kinematic:                               | 411.600 mm <sup>2</sup> /s           |              |
| Solubility in water:                                | No applicable information available. |              |
| Miscibility with water:                             | immiscible                           |              |
| Solubility (quantitative):                          | No applicable information available. |              |
| Solubility (qualitative):                           | No applicable information available. |              |
| Molar mass:                                         | No applicable information available. |              |
| Evaporation rate:                                   | No applicable information available. |              |

# Safety Data Sheet

## SC90 UNO HD WHITE.

Revision date : 2021/06/07  
Version: 6.0

Page: 8/12  
(30669052/SDS\_GEN\_CA/EN)

### 10. Stability and Reactivity

#### Reactivity

No applicable information available.

#### Chemical stability

The product is chemically stable.

#### Possibility of hazardous reactions

No applicable information available.

#### Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge.

#### Incompatible materials

strong oxidizing agents, strong bases, strong acids

#### Hazardous decomposition products

Decomposition products:  
carbon dioxide, carbon monoxide

Thermal decomposition:  
No applicable information available.

### 11. Toxicological information

#### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

#### Primary routes of entry

Solvents are absorbed through the skin.

#### Acute Toxicity/Effects

##### Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact.

##### *Information on: 1,2,4-trimethylbenzene*

*Assessment of acute toxicity: Virtually nontoxic after a single skin contact. Virtually nontoxic after a single ingestion. Of moderate toxicity after short-term inhalation. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.*

##### *Information on: ethylbenzene*

*Assessment of acute toxicity: Of moderate toxicity after short-term inhalation. Virtually nontoxic after a single skin contact. Of low toxicity after single ingestion.*

##### *Information on: Xylene*

*Assessment of acute toxicity: Of low toxicity after single ingestion. Of low toxicity after short-term inhalation. Virtually nontoxic after a single skin contact. The European Union (EU) has classified this*



# Safety Data Sheet

## SC90 UNO HD WHITE.

Revision date : 2021/06/07  
Version: 6.0

Page: 9/12  
(30669052/SDS\_GEN\_CA/EN)

*substance as 'harmful' after inhalation. The European Union (EU) has classified this substance as 'harmful' after dermal exposure. High concentrations in the air may cause narcosis.*

*Information on: Solvent naphtha (petroleum), light arom.*

*Assessment of acute toxicity: Virtually nontoxic after a single ingestion. No deaths at the highest dose tested after short-term inhalation. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. Of low toxicity after short-term skin contact.*

### Oral

Type of value: LD50

Species: rat

Value: > 2,000.000000 mg/kg

### Inhalation

Type of value: LC50

Species: rat

Value: > 21.100000 mg/l

### Dermal

Type of value: LD50

Species: rabbit

Value: > 4,300.000000 mg/kg

### Assessment other acute effects

No applicable information available.

### Irritation / corrosion

Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.

*Information on: 1,2,4-trimethylbenzene*

*Assessment of irritating effects: Skin contact causes irritation. Eye contact causes irritation. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

*Information on: ethylbenzene*

*Assessment of irritating effects: May cause slight irritation to the skin. May cause slight irritation to the eyes.*

*Information on: mesitylene*

*Assessment of irritating effects: Not irritating to the skin. Eye contact causes irritation.*

*Information on: n-Butyl acetate*

*Assessment of irritating effects: Not irritating to the skin. Not irritating to the eyes.*

*Not irritating to the skin. May cause slight irritation to the eyes.*

*Information on: Xylene*

*Assessment of irritating effects: Skin contact causes irritation. Eye contact causes irritation.*

*Information on: Solvent naphtha (petroleum), light arom.*

*Assessment of irritating effects: May cause slight irritation to the skin. May cause slight irritation to the eyes. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

### Aspiration Hazard

No applicable information available.

# Safety Data Sheet

## SC90 UNO HD WHITE.

Revision date : 2021/06/07  
Version: 6.0

Page: 10/12  
(30669052/SDS\_GEN\_CA/EN)

### Chronic Toxicity/Effects

#### Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure may affect certain organs.

#### *Information on: ethylbenzene*

*Assessment of repeated dose toxicity: The substance may cause damage to the liver after repeated ingestion of high doses, as shown in animal studies. The substance may cause deafness after repeated inhalation. The substance may cause deafness after repeated ingestion.*

#### *Information on: n-Butyl acetate*

*Assessment of repeated dose toxicity: After repeated exposure the prominent effect is local irritation.*

#### *Information on: Xylene*

*Assessment of repeated dose toxicity: Overexposure may cause liver and kidney toxicity. Repeated exposure may affect certain organs. Damages the central nerve system. The substance can cause changes in the following organs after repeated exposure to large quantities: Liver Kidney*

#### *Information on: Solvent naphtha (petroleum), light arom.*

*Assessment of repeated dose toxicity: After repeated exposure the prominent effect is local irritation. The substance may cause damage to the liver after repeated ingestion. Effects on the kidney of male rats were detected after repeated exposure. These effects are specific for the male rat and are known to be of no relevance to humans. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

#### *Information on: quartz, crystalline*

*Assessment of repeated dose toxicity: Prolonged or repeated inhalation of respirable crystalline silica may result in silicosis. Repeated inhalation exposure may cause inflammatory effects in the lung. The substance may cause increase in lung mass and lung tissue changes after repeated inhalation. This product may contain greater than 0.1% crystalline silica. Repeated exposure to high concentrations results in silicosis, a lung disease characterized by coughing, difficult breathing, wheezing, scarring of the lungs, and repeated, non-specific chest illnesses.*

-----

#### Carcinogenicity

Assessment of carcinogenicity: Contains a suspect carcinogen.

#### *Information on: ethylbenzene*

*Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. The effect is caused by an animal specific mechanism that has no human counter part. A clear indication of an increased risk of cancer in humans has so far not been shown. IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).*

#### *Information on: quartz, crystalline*

*Assessment of carcinogenicity: May cause cancer by inhalation. The substance was found to cause cancer in animal experiments. Epidemiological studies stated a carcinogenic activity also in humans. The substance and its compounds in the form of respirable dusts/aerosols classified by the German MAK commission as a category 1 carcinogen (substances that cause cancer to humans). The International Agency for Research on Cancer (IARC) has classified this substance as a Group 1 (known) human carcinogen. NTP listed carcinogen*

#### *Information on: Titanium oxide (TiO<sub>2</sub>)*

*Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. EU-classification IARC (International Agency for Research on Cancer) has classified this substance as*

# Safety Data Sheet

## SC90 UNO HD WHITE.

Revision date : 2021/06/07  
Version: 6.0

Page: 11/12  
(30669052/SDS\_GEN\_CA/EN)

*group 2B (The agent is possibly carcinogenic to humans). In long-term studies in rats in which the substance was given by inhalation, a carcinogenic effect was observed. Tumors were only observed in rats after chronic inhalative exposure to high concentrations which caused sustained lung inflammation. In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. Dermal exposure is not expected to be carcinogenic.*

-----

### Teratogenicity

*Information on: Xylene*

*Assessment of teratogenicity: In animal studies the substance did not cause malformations.*

-----

---

## 12. Ecological Information

No applicable information available.

---

## 13. Disposal considerations

### **Waste disposal of substance:**

Do not incinerate closed containers. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. Do not discharge into drains/surface waters/groundwater.

Must be disposed of or incinerated in accordance with local regulations.

### **Container disposal:**

Do not reuse containers without commercial reconditioning. WARNING: Empty containers may still contain hazardous residue.

---

## 14. Transport Information

### **Land transport**

TDG

|                       |         |
|-----------------------|---------|
| Hazard class:         | 3       |
| Packing group:        | III     |
| ID number:            | UN 1263 |
| Hazard label:         | 3       |
| Proper shipping name: | PAINT   |

### **Sea transport**

IMDG

|                       |         |
|-----------------------|---------|
| Hazard class:         | 3       |
| Packing group:        | III     |
| ID number:            | UN 1263 |
| Hazard label:         | 3       |
| Marine pollutant:     | NO      |
| Proper shipping name: | PAINT   |

### **Air transport**

IATA/ICAO

# Safety Data Sheet

## SC90 UNO HD WHITE.

Revision date : 2021/06/07

Version: 6.0

Page: 12/12

(30669052/SDS\_GEN\_CA/EN)

|                       |         |
|-----------------------|---------|
| Hazard class:         | 3       |
| Packing group:        | III     |
| ID number:            | UN 1263 |
| Hazard label:         | 3       |
| Proper shipping name: | PAINT   |

---

## 15. Regulatory Information

### Federal Regulations

#### Registration status:

Chemical DSL, CA released / listed

#### NFPA Hazard codes:

Health: 2 Fire: 3 Reactivity: 0 Special:

---

## 16. Other Information

#### SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2021/06/07

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

---

END OF DATA SHEET