

## 20216, 22040 LM48 Installation Paste 50g, 1kg

### Liqui Moly GmbH

Chemwatch: 64-93541

Version No: 3.1

Safety Data Sheet according to WHMIS 2015 requirements

Chemwatch Hazard Alert Code: 1

Issue Date: 01/11/2019

Print Date: 08/11/2021

S.GHS.CAN.EN

## SECTION 1 Identification

### Product Identifier

Product name	20216, 22040 LM48 Installation Paste 50g, 1kg
Chemical Name	Not Applicable
Synonyms	Not Available
Chemical formula	Not Applicable
Other means of identification	Not Available

### Recommended use of the chemical and restrictions on use

Relevant identified uses	Use according to manufacturer's directions.
--------------------------	---

### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	Liqui Moly GmbH
Address	Jerg-Wieland-Strasse 4 Ulm D-89081 Germany
Telephone	+49 731 1420 0
Fax	+49 731 1420 82
Website	<a href="http://www.liqui-moly.com/">http://www.liqui-moly.com/</a>
Email	Not Available

### Emergency phone number

Association / Organisation	INFOTRAC
Emergency telephone numbers	+1800 535 5053 (US, Canada & Mexico)
Other emergency telephone numbers	+1 352 323 3500 (International)

## SECTION 2 Hazard(s) identification

### Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

### Canadian WHMIS Symbols

Classification	Not Applicable
----------------	----------------

### Label elements

Hazard pictogram(s)	Not Applicable
Signal word	Not Applicable

### Hazard statement(s)

Not Applicable

### Physical and Health hazard(s) not otherwise classified

Not Applicable

**Precautionary statement(s) Prevention**

Not Applicable

**Precautionary statement(s) Response**

Not Applicable

**Precautionary statement(s) Storage**

Not Applicable

**Precautionary statement(s) Disposal**

Not Applicable

**SECTION 3 Composition / information on ingredients****Substances**

See section below for composition of Mixtures

**Mixtures**

CAS No	%[weight]	Name
64741-88-4.	>50	<u>paraffinic distillate, heavy, solvent-refined (severe)</u>
7782-42-5	<20	<u>graphite, natural</u>
1314-98-3	<15	<u>zinc sulfide</u>
7789-75-5	<5	<u>calcium fluoride</u>
1302-78-9	<5	<u>bentonite</u>

**SECTION 4 First-aid measures****Description of first aid measures**

<b>Eye Contact</b>	<p>If this product comes in contact with eyes:</p> <ul style="list-style-type: none"> <li>▶ Wash out immediately with water.</li> <li>▶ If irritation continues, seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
<b>Skin Contact</b>	<p>If skin or hair contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>
<b>Inhalation</b>	<ul style="list-style-type: none"> <li>▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>▶ Other measures are usually unnecessary.</li> </ul>
<b>Ingestion</b>	<ul style="list-style-type: none"> <li>▶ Immediately give a glass of water.</li> <li>▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>

**Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

- ▶ Heavy and persistent skin contamination over many years may lead to dysplastic changes. Pre-existing skin disorders may be aggravated by exposure to this product.
- ▶ In general, emesis induction is unnecessary with high viscosity, low volatility products, i.e. most oils and greases.
- ▶ High pressure accidental injection through the skin should be assessed for possible incision, irrigation and/or debridement.

**NOTE:** Injuries may not seem serious at first, but within a few hours tissue may become swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Product may be forced through considerable distances along tissue planes.

**SECTION 5 Fire-fighting measures****Extinguishing media**

- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.
- ▶ Water spray or fog - Large fires only.

**Special hazards arising from the substrate or mixture**

<b>Fire Incompatibility</b>	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

**Special protective equipment and precautions for fire-fighters**

<b>Fire Fighting</b>	<ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water courses.</li> <li>▶ Use water delivered as a fine spray to control fire and cool adjacent area.</li> <li>▶ <b>DO NOT</b> approach containers suspected to be hot.</li> <li>▶ Cool fire exposed containers with water spray from a protected location.</li> <li>▶ If safe to do so, remove containers from path of fire.</li> <li>▶ Equipment should be thoroughly decontaminated after use.</li> </ul>
<b>Fire/Explosion Hazard</b>	<ul style="list-style-type: none"> <li>▶ Combustible.</li> <li>▶ Slight fire hazard when exposed to heat or flame.</li> <li>▶ Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>▶ On combustion, may emit toxic fumes of carbon monoxide (CO).</li> <li>▶ May emit acrid smoke.</li> <li>▶ Mists containing combustible materials may be explosive.</li> </ul>

Continued...

## 20216, 22040 LM48 Installation Paste 50g, 1kg

Combustion products include:  
carbon monoxide (CO)  
carbon dioxide (CO<sub>2</sub>)  
sulfur oxides (SO<sub>x</sub>)  
metal oxides  
other pyrolysis products typical of burning organic material.  
**CARE:** Water in contact with hot liquid may cause foaming and a steam explosion with wide scattering of hot oil and possible severe burns.  
Foaming may cause overflow of containers and may result in possible fire.

## SECTION 6 Accidental release measures

## Personal precautions, protective equipment and emergency procedures

See section 8

## Environmental precautions

See section 12

## Methods and material for containment and cleaning up

Minor Spills	Slippery when spilt. ▶ Clean up all spills immediately. ▶ Avoid contact with skin and eyes. ▶ Wear impervious gloves and safety goggles. ▶ Trowel up/scrape up. ▶ Place spilled material in clean, dry, sealed container. ▶ Flush spill area with water.
Major Spills	▶ Clear area of personnel and move upwind. ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Control personal contact with the substance, by using protective equipment. ▶ Prevent spillage from entering drains, sewers or water courses. ▶ Recover product wherever possible. ▶ Put residues in labelled containers for disposal. ▶ If contamination of drains or waterways occurs, advise emergency services. Slippery when spilt.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 Handling and storage

## Precautions for safe handling

Safe handling	▶ Limit all unnecessary personal contact. ▶ Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area. ▶ Avoid contact with incompatible materials. ▶ When handling, <b>DO NOT eat, drink or smoke.</b> ▶ Keep containers securely sealed when not in use. ▶ Avoid physical damage to containers. ▶ Always wash hands with soap and water after handling. ▶ Work clothes should be laundered separately. ▶ Use good occupational work practice. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. ▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
Other information	▶ Store in original containers. ▶ Keep containers securely sealed. ▶ Store in a cool, dry, well-ventilated area. ▶ Store away from incompatible materials and foodstuff containers. ▶ Protect containers against physical damage and check regularly for leaks. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

## Conditions for safe storage, including any incompatibilities

Suitable container	▶ Metal can or drum ▶ Packaging as recommended by manufacturer. ▶ Check all containers are clearly labelled and free from leaks.
Storage incompatibility	Avoid contamination of water, foodstuffs, feed or seed. · <b>CARE:</b> Water in contact with heated material may cause foaming or a steam explosion with possible severe burns from wide scattering of hot material. Resultant overflow of containers may result in fire. · Oil leaks in a pressurized circuit may result in a fine flammable spray (the lower flammability limit for oil mist is reached for a concentration of about 45 g/m <sup>3</sup> ) · Autoignition temperatures may be significantly lower under particular conditions (slow oxidation on finely divided materials.. ▶ Avoid reaction with oxidising agents

## SECTION 8 Exposure controls / personal protection

## Control parameters

## Occupational Exposure Limits (OEL)

## INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Canada - Yukon Permissible	paraffinic	Oil mist, mineral	5	10	Not	Not Available

Continued...

## 20216, 22040 LM48 Installation Paste 50g, 1kg

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Concentrations for Airborne Contaminant Substances	distillate, heavy, solvent-refined (severe)		mg/m3	mg/m3	Available	
Canada - Nova Scotia Occupational Exposure Limits	paraffinic distillate, heavy, solvent-refined (severe)	Oil mist - mineral	5 mg/m3	10 mg/m3	Not Available	TLV Basis: lung. As sampled by method that does not collect vapor.
Canada - Alberta Occupational Exposure Limits	paraffinic distillate, heavy, solvent-refined (severe)	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	paraffinic distillate, heavy, solvent-refined (severe)	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Manitoba Occupational Exposure Limits	paraffinic distillate, heavy, solvent-refined (severe)	Not Available	5 mg/m3	Not Available	Not Available	TLV® Basis: URT irr
Canada - British Columbia Occupational Exposure Limits	paraffinic distillate, heavy, solvent-refined (severe)	Oil mist - mineral, severely refined	1 mg/m3	Not Available	Not Available	Not Available
Canada - Prince Edward Island Occupational Exposure Limits	paraffinic distillate, heavy, solvent-refined (severe)	Mineral oil, excluding metal working fluids - Pure, highly and severely refined	5 mg/m3	Not Available	Not Available	TLV® Basis: URT irr
Canada - Northwest Territories Occupational Exposure Limits	paraffinic distillate, heavy, solvent-refined (severe)	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	paraffinic distillate, heavy, solvent-refined (severe)	Mineral oil (mist)	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	graphite, natural	Graphite - All forms except graphite fibres	2 mg/m3	Not Available	Not Available	TLV Basis: pneumoconiosis
Canada - Alberta Occupational Exposure Limits	graphite, natural	Graphite, respirable (all forms except graphite fibres)	2 mg/m3	Not Available	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	graphite, natural	Graphite, natural-all forms except graphite fibres (respirable fraction++)	2 mg/m3	4 mg/m3	Not Available	Not Available
Canada - Manitoba Occupational Exposure Limits	graphite, natural	Not Available	2 mg/m3	Not Available	Not Available	TLV® Basis: Pneumoconiosis
Canada - British Columbia Occupational Exposure Limits	graphite, natural	Graphite - All forms except graphite fibres, Respirable	2 mg/m3	Not Available	Not Available	Not Available
Canada - Prince Edward Island Occupational Exposure Limits	graphite, natural	Graphite (all forms except graphite fibres)	2 mg/m3	Not Available	Not Available	TLV® Basis: Pneumoconiosis
Canada - Ontario Occupational Exposure Limits	graphite, natural	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified (PNOS) (Inhalable fraction)	10 mg/m3	Not Available	Not Available	(I) Inhalable fraction: means that size fraction of the airborne particulate deposited anywhere in the respiratory tract and collected during air sampling with a particle size-selective device that, (a) meets the ACGIH particle size-selective sampling criteria for airborne particulate matter; and (b) has the cut point of 100 µm at 50 per cent collection efficiency.
Canada - Ontario Occupational Exposure Limits	graphite, natural	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified (PNOS) (Respirable fraction)	3 mg/m3	Not Available	Not Available	(R) Respirable fraction: means that size fraction of the airborne particulate deposited in the gas-exchange region of the respiratory tract and collected during air sampling with a particle size-selective device that, (a) meets the ACGIH particle size-selective sampling criteria for airborne particulate matter; and (b) has the cut point of 4 µm at 50 per cent collection efficiency.

## 20216, 22040 LM48 Installation Paste 50g, 1kg

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Canada - Northwest Territories Occupational Exposure Limits	graphite, natural	Graphite, natural-all forms except graphite fibres (respirable fraction)	2 mg/m3	4 mg/m3	Not Available	Not Available
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	graphite, natural	Graphite (all forms except fibers)	2 mg/m3	Not Available	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	zinc sulfide	Particles (Insoluble or Poorly Soluble) [NOS] Inhalable particles	10 mg/m3	Not Available	Not Available	See Appendix B current TLV/BEI Book
Canada - Nova Scotia Occupational Exposure Limits	zinc sulfide	Particles (Insoluble or Poorly Soluble) [NOS] Respirable particles	3 mg/m3	Not Available	Not Available	See Appendix B current TLV/BEI Book
Canada - Alberta Occupational Exposure Limits	zinc sulfide	Particulate Not Otherwise Regulated - Total	10 mg/m3	Not Available	Not Available	Not Available
Canada - Alberta Occupational Exposure Limits	zinc sulfide	Particulate Not Otherwise Regulated - Respirable	3 mg/m3	Not Available	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	zinc sulfide	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified: Respirable fraction++	3 mg/m3	6 mg/m3	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	zinc sulfide	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified: Inhalable fraction++	10 mg/m3	20 mg/m3	Not Available	Not Available
Canada - Ontario Occupational Exposure Limits	zinc sulfide	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified (PNOS) (Inhalable fraction)	10 mg/m3	Not Available	Not Available	(I) Inhalable fraction: means that size fraction of the airborne particulate deposited anywhere in the respiratory tract and collected during air sampling with a particle size-selective device that, (a) meets the ACGIH particle size-selective sampling criteria for airborne particulate matter; and (b) has the cut point of 100 µm at 50 per cent collection efficiency.
Canada - Ontario Occupational Exposure Limits	zinc sulfide	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified (PNOS) (Respirable fraction)	3 mg/m3	Not Available	Not Available	(R) Respirable fraction: means that size fraction of the airborne particulate deposited in the gas-exchange region of the respiratory tract and collected during air sampling with a particle size-selective device that, (a) meets the ACGIH particle size-selective sampling criteria for airborne particulate matter; and (b) has the cut point of 4 µm at 50 per cent collection efficiency.
Canada - Northwest Territories Occupational Exposure Limits	zinc sulfide	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified: Inhalable fraction	10 mg/m3	20 mg/m3	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits	zinc sulfide	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified: Respirable fraction	3 mg/m3	6 mg/m3	Not Available	Not Available
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	zinc sulfide	Particulates Not Otherwise Classified (PNOC)	10 mg/m3	Not Available	Not Available	Not Available
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	calcium fluoride	Fluoride (as F)	2.5 mg/m3	2.5 mg/m3	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	calcium fluoride	Fluorides (as F)	2.5 mg/m3	Not Available	Not Available	TLV Basis: bone damage; fluorosis. BEI
Canada - Alberta Occupational Exposure Limits	calcium fluoride	Fluorides, as F	2.5 mg/m3	Not Available	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	calcium fluoride	Fluoride, (as F)	2.5 mg/m3	5 mg/m3	Not Available	Not Available
Canada - Manitoba Occupational Exposure Limits	calcium fluoride	Not Available	2.5 mg/m3	Not Available	Not Available	TLV® Basis: Bone dam; fluorosis; BEI
Canada - British Columbia Occupational Exposure Limits	calcium fluoride	Fluorides (as F)	2.5 mg/m3	Not Available	Not Available	Not Available
Canada - Prince Edward Island Occupational Exposure Limits	calcium fluoride	Fluorides, as F	2.5 mg/m3	Not Available	Not Available	TLV® Basis: Bone dam; fluorosis; BEI
Canada - Northwest Territories Occupational Exposure Limits	calcium fluoride	Fluoride, (as F)	2.5 mg/m3	5 mg/m3	Not Available	Not Available

Continued...

## 20216, 22040 LM48 Installation Paste 50g, 1kg

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	calcium fluoride	Fluorides (as F)	2.5 mg/m3	Not Available	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	bentonite	Particles (Insoluble or Poorly Soluble) [NOS] Inhalable particles	10 mg/m3	Not Available	Not Available	See Appendix B current TLV/BEI Book
Canada - Nova Scotia Occupational Exposure Limits	bentonite	Particles (Insoluble or Poorly Soluble) [NOS] Respirable particles	3 mg/m3	Not Available	Not Available	See Appendix B current TLV/BEI Book
Canada - Alberta Occupational Exposure Limits	bentonite	Particulate Not Otherwise Regulated - Respirable	3 mg/m3	Not Available	Not Available	Not Available
Canada - Alberta Occupational Exposure Limits	bentonite	Particulate Not Otherwise Regulated - Total	10 mg/m3	Not Available	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	bentonite	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified: Respirable fraction++	3 mg/m3	6 mg/m3	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	bentonite	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified: Inhalable fraction++	10 mg/m3	20 mg/m3	Not Available	Not Available
Canada - Ontario Occupational Exposure Limits	bentonite	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified (PNOS) (Respirable fraction)	3 mg/m3	Not Available	Not Available	(R) Respirable fraction: means that size fraction of the airborne particulate deposited in the gas-exchange region of the respiratory tract and collected during air sampling with a particle size-selective device that, (a) meets the ACGIH particle size-selective sampling criteria for airborne particulate matter; and (b) has the cut point of 4 µm at 50 per cent collection efficiency.
Canada - Ontario Occupational Exposure Limits	bentonite	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified (PNOS) (Inhalable fraction)	10 mg/m3	Not Available	Not Available	(I) Inhalable fraction: means that size fraction of the airborne particulate deposited anywhere in the respiratory tract and collected during air sampling with a particle size-selective device that, (a) meets the ACGIH particle size-selective sampling criteria for airborne particulate matter; and (b) has the cut point of 100 µm at 50 per cent collection efficiency.
Canada - Northwest Territories Occupational Exposure Limits	bentonite	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified: Inhalable fraction	10 mg/m3	20 mg/m3	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits	bentonite	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified: Respirable fraction	3 mg/m3	6 mg/m3	Not Available	Not Available
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	bentonite	Particulates Not Otherwise Classified (PNOC)	10 mg/m3	Not Available	Not Available	Not Available

## Emergency Limits


Ingredient	TEEL-1	TEEL-2	TEEL-3
paraffinic distillate, heavy, solvent-refined (severe)	140 mg/m3	1,500 mg/m3	8,900 mg/m3
graphite, natural	6 mg/m3	330 mg/m3	2,000 mg/m3
zinc sulfide	8.9 mg/m3	99 mg/m3	590 mg/m3
calcium fluoride	15 mg/m3	170 mg/m3	1,000 mg/m3

Ingredient	Original IDLH	Revised IDLH
paraffinic distillate, heavy, solvent-refined (severe)	2,500 mg/m3	Not Available
graphite, natural	1,250 mg/m3	Not Available
zinc sulfide	Not Available	Not Available
calcium fluoride	250 mg/m3	Not Available
bentonite	Not Available	Not Available

## Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:
----------------------------------	---

## 20216, 22040 LM48 Installation Paste 50g, 1kg

	<p>Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.</p> <table border="1"> <thead> <tr> <th>Type of Contaminant:</th><th>Air Speed:</th></tr> </thead> <tbody> <tr> <td>solvent, vapours, degreasing etc., evaporating from tank (in still air)</td><td>0.25-0.5 m/s (50-100 f/min)</td></tr> <tr> <td>aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)</td><td>0.5-1 m/s (100-200 f/min.)</td></tr> <tr> <td>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</td><td>1-2.5 m/s (200-500 f/min)</td></tr> <tr> <td>grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).</td><td>2.5-10 m/s (500-2000 f/min.)</td></tr> </tbody> </table> <p>Within each range the appropriate value depends on:</p> <table border="1"> <thead> <tr> <th>Lower end of the range</th><th>Upper end of the range</th></tr> </thead> <tbody> <tr> <td>1: Room air currents minimal or favourable to capture</td><td>1: Disturbing room air currents</td></tr> <tr> <td>2: Contaminants of low toxicity or of nuisance value only</td><td>2: Contaminants of high toxicity</td></tr> <tr> <td>3: Intermittent, low production.</td><td>3: High production, heavy use</td></tr> <tr> <td>4: Large hood or large air mass in motion</td><td>4: Small hood - local control only</td></tr> </tbody> </table> <p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p>	Type of Contaminant:	Air Speed:	solvent, vapours, degreasing etc., evaporating from tank (in still air)	0.25-0.5 m/s (50-100 f/min)	aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)	direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min)	grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)	Lower end of the range	Upper end of the range	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents	2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity	3: Intermittent, low production.	3: High production, heavy use	4: Large hood or large air mass in motion	4: Small hood - local control only
Type of Contaminant:	Air Speed:																				
solvent, vapours, degreasing etc., evaporating from tank (in still air)	0.25-0.5 m/s (50-100 f/min)																				
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)																				
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min)																				
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)																				
Lower end of the range	Upper end of the range																				
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents																				
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity																				
3: Intermittent, low production.	3: High production, heavy use																				
4: Large hood or large air mass in motion	4: Small hood - local control only																				
Personal protection																					
Eye and face protection	<ul style="list-style-type: none"> <li>▶ Safety glasses with side shields</li> <li>▶ Chemical goggles.</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> </ul>																				
Skin protection	See Hand protection below																				
Hands/feet protection	Wear general protective gloves, eg. light weight rubber gloves.																				
Body protection	See Other protection below																				
Other protection	<p>No special equipment needed when handling small quantities.</p> <p><b>OTHERWISE:</b></p> <ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ Barrier cream.</li> <li>▶ Eyewash unit.</li> </ul>																				

## Recommended material(s)

## GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

**"Forsberg Clothing Performance Index"**.

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

20216, 22040 LM48 Installation Paste 50g, 1kg

Material	CPI
BUTYL	A
BUTYL/NEOPRENE	A
PE/EVAL/PE	A
PVDC/PE/PVDC	A
SARANEX-23 2-PLY	B
TEFLON	B
CPE	C
HYPALON	C

## Respiratory protection

Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AX-AUS P2	-	AX-PAPR-AUS / Class 1 P2
up to 50 x ES	-	AX-AUS / Class 1 P2	-
up to 100 x ES	-	AX-2 P2	AX-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur

Continued...



## 20216, 22040 LM48 Installation Paste 50g, 1kg

NATURAL RUBBER	C
NATURAL+NEOPRENE	C
NEOPRENE	C
NITRILE	C
NITRILE+PVC	C
PVA	C
PVC	C
SARANEX-23	C
VITON/NEOPRENE	C

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

## SECTION 9 Physical and chemical properties

## Information on basic physical and chemical properties

<b>Appearance</b>	Black paste.		
<b>Physical state</b>	Non Slump Paste	<b>Relative density (Water = 1)</b>	1.0
<b>Odour</b>	Not Available	<b>Partition coefficient n-octanol / water</b>	Not Available
<b>Odour threshold</b>	Not Available	<b>Auto-ignition temperature (°C)</b>	Not Available
<b>pH (as supplied)</b>	Not Available	<b>Decomposition temperature</b>	Not Available
<b>Melting point / freezing point (°C)</b>	Not Available	<b>Viscosity (cSt)</b>	Not Available
<b>Initial boiling point and boiling range (°C)</b>	Not Available	<b>Molecular weight (g/mol)</b>	Not Applicable
<b>Flash point (°C)</b>	101	<b>Taste</b>	Not Available
<b>Evaporation rate</b>	Not Available	<b>Explosive properties</b>	Not Available
<b>Flammability</b>	Not Applicable	<b>Oxidising properties</b>	Not Available
<b>Upper Explosive Limit (%)</b>	Not Available	<b>Surface Tension (dyn/cm or mN/m)</b>	Not Available
<b>Lower Explosive Limit (%)</b>	Not Available	<b>Volatile Component (%vol)</b>	Not Available
<b>Vapour pressure (kPa)</b>	Not Available	<b>Gas group</b>	Not Available
<b>Solubility in water</b>	Not Available	<b>pH as a solution (%)</b>	Not Available
<b>Vapour density (Air = 1)</b>	Not Available	<b>VOC g/L</b>	Not Available

## SECTION 10 Stability and reactivity

<b>Reactivity</b>	See section 7
<b>Chemical stability</b>	Product is considered stable and hazardous polymerisation will not occur.
<b>Possibility of hazardous reactions</b>	See section 7
<b>Conditions to avoid</b>	See section 7
<b>Incompatible materials</b>	See section 7
<b>Hazardous decomposition products</b>	See section 5

## SECTION 11 Toxicological information

## Information on toxicological effects

<b>Inhaled</b>	Inhalation hazard is increased at higher temperatures. Not normally a hazard due to non-volatile nature of product Inhalation of oil droplets or aerosols may cause discomfort and may produce chemical inflammation of the lungs.
<b>Ingestion</b>	The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
<b>Skin Contact</b>	The liquid may be able to be mixed with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives. Open cuts, abraded or irritated skin should not be exposed to this material The material may accentuate any pre-existing dermatitis condition Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin



## 20216, 22040 LM48 Installation Paste 50g, 1kg

	prior to the use of the material and ensure that any external damage is suitably protected.	
<b>Eye</b>	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).	
<b>Chronic</b>	Oil may contact the skin or be inhaled. Extended exposure can lead to eczema, inflammation of hair follicles, pigmentation of the face and warts on the soles of the feet.	
<b>20216, 22040 LM48 Installation Paste 50g, 1kg</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	Not Available	Not Available
<b>paraffinic distillate, heavy, solvent-refined (severe)</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	Dermal (rabbit) LD50: >2000 mg/kg <sup>[2]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
	Inhalation(Rat) LC50; 2.18 mg/l4h <sup>[2]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
	Oral(Rat) LD50; >5000 mg/kg <sup>[2]</sup>	
<b>graphite, natural</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	Inhalation(Rat) LC50; >2 mg/L4h <sup>[1]</sup>	Eye (rabbit): non-irritant *
	Oral(Rat) LD50; >2000 mg/kg <sup>[1]</sup>	Eye : Not irritating
		Skin (rabbit): 4 h non-irritant *
<b>zinc sulfide</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	dermal (rat) LD50: >2000 mg/kg <sup>[2]</sup>	Not Available
	Inhalation(Rat) LC50; >5.04 mg/L4h <sup>[2]</sup>	
	Oral(Rat) LD50; >2000 mg/kg <sup>[1]</sup>	
<b>calcium fluoride</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	dermal (rat) LD50: >905 mg/kg <sup>[1]</sup>	Not Available
	Inhalation(Rat) LC50; 0.29 mg/l4h <sup>[1]</sup>	
	Oral(Rat) LD50; 101 mg/kg <sup>[1]</sup>	
<b>bentonite</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	Oral(Cat) LD50; >1.25 mg/kg <sup>[2]</sup>	Not Available
<b>Legend:</b>	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

<b>PARAFFINIC DISTILLATE, HEAVY, SOLVENT-REFINED (SEVERE)</b>	<p>The materials included in the Lubricating Base Oils category are related from both process and physical-chemical perspectives; The potential toxicity of a specific distillate base oil is inversely related to the severity or extent of processing the oil has undergone, since:</p> <ul style="list-style-type: none"> <li>The adverse effects of these materials are associated with undesirable components, and</li> <li>The levels of the undesirable components are inversely related to the degree of processing;</li> <li>Distillate base oils receiving the same degree or extent of processing will have similar toxicities;</li> <li>The potential toxicity of residual base oils is independent of the degree of processing the oil receives.</li> <li>The reproductive and developmental toxicity of the distillate base oils is inversely related to the degree of processing.</li> </ul> <p>Unrefined &amp; mildly refined distillate base oils contain the highest levels of undesirable components, have the largest variation of hydrocarbon molecules and have shown the highest potential cancer-causing and mutation-causing activities. Highly and severely refined distillate base oils are produced from unrefined and mildly refined oils by removing or transforming undesirable components. In comparison to unrefined and mildly refined base oils, the highly and severely refined distillate base oils have a smaller range of hydrocarbon molecules and have demonstrated very low mammalian toxicity. Testing of residual oils for mutation-causing and cancer-causing potential has shown negative results, supporting the belief that these materials lack biologically active components or the components are largely non-bioavailable due to their molecular size. Toxicity testing has consistently shown that lubricating base oils have low acute toxicities. Numerous tests have shown that a lubricating base oil's mutagenic and carcinogenic potential correlates with its 3-7 ring polycyclic aromatic compound (PAC) content, and the level of DMSO extractables (e.g. IP346 assay), both characteristics that are directly related to the degree/conditions of processing.</p> <p>For highly and severely refined distillate base oils:</p> <p>In animal studies, the acute, oral, semilethal dose is &gt;5g/kg body weight and the semilethal dose by skin contact is &gt;2g/kg body weight. The semilethal concentration for inhalation is 2.18 to &gt;4 mg/L. The materials have varied from "non-irritating" to "moderately irritating" when tested for skin and eye irritation. Testing for sensitisation has been negative. The effects of repeated exposure vary by species; in animals, effects to the testes and lung have been observed, as well as the formation of granulomas. In animals, these substances have not been found to cause reproductive toxicity or significant increases in birth defects. They are also not considered to cause cancer, mutations or chromosome aberrations.</p> <p>The substance is classified by IARC as Group 3:  <b>NOT</b> classifiable as to its carcinogenicity to humans.  Evidence of carcinogenicity may be inadequate or limited in animal testing.</p>
<b>GRAPHITE, NATURAL</b>	* Timal MSDS
<b>BENTONITE</b>	<p>For bentonite clays:</p> <p>Bentonite (CAS No. 1302-78-9) consists of a group of clays formed by crystallization of vitreous volcanic ashes that were deposited in water. The expected acute oral toxicity of bentonite in humans is very low. However, when bentonite had been used as a prophylactic paste, larger amounts caused severe eye injury, including abscesses behind the cornea. In animals, large amounts caused decreased growth, muscle weakness and death with marked changes in both calcium and phosphorus metabolism.</p> <p>Bentonite, in animals, caused lung scarring if instilled into the windpipe. Bentonite clay dust is believed to be responsible for asthma in workers in an American processing plant.</p> <p>Swallowing bentonite without adequate liquids may result in intestinal obstruction in humans.</p> <p>Chronically swallowing bentonite has been reported to cause muscle inflammation.</p>

<b>PARAFFINIC DISTILLATE, HEAVY, SOLVENT-REFINED (SEVERE) &amp; ZINC SULFIDE &amp; BENTONITE</b>	No significant acute toxicological data identified in literature search.		
<b>GRAPHITE, NATURAL &amp; CALCIUM FLUORIDE &amp; BENTONITE</b>	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.		
<b>Acute Toxicity</b>	✗	<b>Carcinogenicity</b>	✗
<b>Skin Irritation/Corrosion</b>	✗	<b>Reproductivity</b>	✗
<b>Serious Eye Damage/Irritation</b>	✗	<b>STOT - Single Exposure</b>	✗
<b>Respiratory or Skin sensitisation</b>	✗	<b>STOT - Repeated Exposure</b>	✗
<b>Mutagenicity</b>	✗	<b>Aspiration Hazard</b>	✗

**Legend:** ✗ – Data either not available or does not fill the criteria for classification  
 ✔ – Data available to make classification

## SECTION 12 Ecological information

### Toxicity

<b>20216, 22040 LM48 Installation Paste 50g, 1kg</b>	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	Not Available	Not Available	Not Available	Not Available	Not Available
<b>paraffinic distillate, heavy, solvent-refined (severe)</b>	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	ErC50	72h	Algae or other aquatic plants	>1000mg/l	1
	NOEC(ECx)	504h	Crustacea	>1mg/l	1
	EC50	48h	Crustacea	>1000mg/l	1
	EC50	96h	Algae or other aquatic plants	>1000mg/l	1
<b>graphite, natural</b>	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	NOEC(ECx)	72h	Algae or other aquatic plants	>=100mg/l	2
	EC50	72h	Algae or other aquatic plants	>100mg/l	2
	LC50	96h	Fish	>100mg/l	2
	EC50	48h	Crustacea	>100mg/l	2
<b>zinc sulfide</b>	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	BCF	1344h	Fish	17-61	7
	LC50	96h	Fish	>0.25mg/l	2
	NOEC(ECx)	96h	Fish	>=0.25mg/l	2
<b>calcium fluoride</b>	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	NOEC(ECx)	504h	Crustacea	3.7mg/l	2
	EC50	72h	Algae or other aquatic plants	>100mg/l	2
	LC50	96h	Fish	>=10.4<=150mg/l	2
	EC50	48h	Crustacea	97mg/l	2
	EC50	96h	Algae or other aquatic plants	43mg/l	2
<b>bentonite</b>	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	EC50	72h	Algae or other aquatic plants	410mg/l	2
	EC50	48h	Crustacea	>10000mg/l	2
	NOEC(ECx)	96h	Fish	<1.4mg/l	2
	EC50(ECx)	72h	Algae or other aquatic plants	>100mg/l	2
	EC50	72h	Algae or other aquatic plants	>100mg/l	2
	EC50	48h	Crustacea	>100mg/l	2
<b>Legend:</b> Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data					

**DO NOT** discharge into sewer or waterways.

Continued...

**Persistence and degradability**

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

**Bioaccumulative potential**

Ingredient	Bioaccumulation
zinc sulfide	LOW (BCF = 217)

**Mobility in soil**

Ingredient	Mobility
	No Data available for all ingredients

**SECTION 13 Disposal considerations****Waste treatment methods**

<b>Product / Packaging disposal</b>	<ul style="list-style-type: none"> <li>▶ <b>DO NOT</b> allow wash water from cleaning or process equipment to enter drains.</li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Recycle wherever possible or consult manufacturer for recycling options.</li> <li>▶ Consult State Land Waste Authority for disposal.</li> <li>▶ Bury or incinerate residue at an approved site.</li> <li>▶ Recycle containers if possible, or dispose of in an authorised landfill.</li> </ul>
-------------------------------------	---

**SECTION 14 Transport information****Labels Required**

<b>Marine Pollutant</b>	NO
-------------------------	----

**Land transport (TDG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS****Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS****Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS****Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

**Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code**

Product name	Group
paraffinic distillate, heavy, solvent-refined (severe)	Not Available
graphite, natural	Not Available
zinc sulfide	Not Available
calcium fluoride	Not Available
bentonite	Not Available

**Transport in bulk in accordance with the ICG Code**

Product name	Ship Type
paraffinic distillate, heavy, solvent-refined (severe)	Not Available
graphite, natural	Not Available
zinc sulfide	Not Available
calcium fluoride	Not Available
bentonite	Not Available

**SECTION 15 Regulatory information****Safety, health and environmental regulations / legislation specific for the substance or mixture**

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations and the SDS contains all the information required by the Hazardous Products Regulations.

**paraffinic distillate, heavy, solvent-refined (severe) is found on the following regulatory lists**

Canada Categorization decisions for all DSL substances  
Canada Domestic Substances List (DSL)

Chemical Footprint Project - Chemicals of High Concern List  
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

**graphite, natural is found on the following regulatory lists**

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS

**zinc sulfide is found on the following regulatory lists**

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS

**calcium fluoride is found on the following regulatory lists**

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Non-Domestic Substances List (NDSL)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

**bentonite is found on the following regulatory lists**

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS

**National Inventory Status**

National Inventory	Status
Australia - AIIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (paraffinic distillate, heavy, solvent-refined (severe); graphite, natural; zinc sulfide; bentonite)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	No (graphite, natural; bentonite)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
<b>Legend:</b>	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

**SECTION 16 Other information**

<b>Revision Date</b>	01/11/2019
<b>Initial Date</b>	10/09/2019

**SDS Version Summary**

Version	Date of Update	Sections Updated
2.1	10/09/2019	Acute Health (skin), Chronic Health, Classification, Environmental, Fire Fighter (fire/explosion hazard), First Aid (skin), Handling Procedure, Ingredients, Personal Protection (other), Personal Protection (eye), Personal Protection (hands/feet), Spills (major), Storage (storage incompatibility), Storage (storage requirement)
3.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification

**Other information****Ingredients with multiple cas numbers**

Name	CAS No
calcium fluoride	7789-75-5, 14542-23-5
bentonite	1302-78-9, 11004-12-9, 10043-07-9, 115628-71-2, 12198-92-4, 12199-69-8, 135945-01-6, 37320-72-2, 52623-66-2, 850872-77-4, 67479-91-8, 89382-86-5, 90989-60-9, 85049-30-5, 97862-66-3, 84776-12-5, 70131-50-9, 90989-59-6

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

**Definitions and abbreviations**

PC—TWA: Permissible Concentration-Time Weighted Average  
 PC—STEL: Permissible Concentration-Short Term Exposure Limit  
 IARC: International Agency for Research on Cancer  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 STEL: Short Term Exposure Limit  
 TEEL: Temporary Emergency Exposure Limit.  
 IDLH: Immediately Dangerous to Life or Health Concentrations  
 ES: Exposure Standard

OSF: Odour Safety Factor  
NOAEL :No Observed Adverse Effect Level  
LOAEL: Lowest Observed Adverse Effect Level  
TLV: Threshold Limit Value  
LOD: Limit Of Detection  
OTV: Odour Threshold Value  
BCF: BioConcentration Factors  
BEI: Biological Exposure Index  
AIIIC: Australian Inventory of Industrial Chemicals  
DSL: Domestic Substances List  
NDL: Non-Domestic Substances List  
IECSC: Inventory of Existing Chemical Substance in China  
EINECS: European INventory of Existing Commercial chemical Substances  
ELINCS: European List of Notified Chemical Substances  
NLP: No-Longer Polymers  
ENCS: Existing and New Chemical Substances Inventory  
KECI: Korea Existing Chemicals Inventory  
NZIoC: New Zealand Inventory of Chemicals  
PICCS: Philippine Inventory of Chemicals and Chemical Substances  
TSCA: Toxic Substances Control Act  
TCSI: Taiwan Chemical Substance Inventory  
INSQ: Inventario Nacional de Sustancias Químicas  
NCI: National Chemical Inventory  
FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.